

STI WIRELESS EXIT STOPPER®



STI-6400WIR

PRODUCT OVERVIEW

The highly effective Exit Stopper can serve as an inexpensive security device and help stop theft by alerting you to any unauthorized exits or entries through emergency exit doors.

HOW IT WORKS

If the protected door is opened, the electronic Exit Stopper emits an ear-piercing alarm for 30 seconds, 3 minutes or continuously (as preset by the user) and sends a wireless signal to the receiver. A key operated override will silence the alarm and allow authorized exits. The unit can be set for a 15 second delay before arming or tripping. Exit Stopper is fitted with a 9 VDC alkaline battery. It is available in red for almost any type of door, mounting or installation, including remote placement of the alarm (not for outdoor use).

KEY FEATURES

General Information

- Alarm alerts to any unauthorized exits/entries through emergency exit doors and rear doors.
- User can select whether to use as an alarm or annunciator.
- When activated, the alarm unit sends a wireless signal to the receiver.

Design

- Highly visible "stop sign" design acts as a deterrent.
- Add warning in second language with provided labels (21 languages).

Construction

- Virtually indestructible polycarbonate housing.
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

Installation

- May be mounted on top, right, left or next to almost any door.
- Recommended operational temperature range is 32° to 113°F.
- For indoor use only.
- Unit is completely self-contained.

Electronics

- 105 or 95 dB warning horn.
- In exit alarm mode, alarm can be set to sound for 30 seconds, 3 minutes or indefinitely (unless disarmed with key supplied or until battery is drained).
- In annunciator mode, device emits 10 short beeps unless the contacts re-engage.
- May be programmed for 15 second entry delay or immediate alarm.
- Arming delay allows unit to arm following authorized exits.

STI Wireless Exit Stopper®

Dimensions and Technical Information

MODELS AVAILABLE

- STI-6400WIR** Wireless Exit Stopper multifunction door alarm
- STI-V6400WIR4** Wireless Exit Stopper multifunction door alarm with 4-Channel Voice Receiver
- STI-6402WIR** Wireless Exit Stopper multifunction door alarm for double door installation

ACCESSORIES

- STI-34098** Single Channel Slave Receiver
- STI-V34104** 4-Channel Voice Receiver
- KIT-E06402** Magnet and reed switch with spacers
- KIT-H19016** Tamper Wrench, set of 2
- KIT-H19032** Replacement keys (2) #2341
- KIT-L16200** Warning “Door Alarmed” label
- KIT-6702** Tamper proof screw and wrench

SPECIFICATIONS

- Housing** 1/8 in. Polycarbonate
- Power Source** 9 VDC Alkaline or 12-24 VDC Wired
- Warning Horn at 1 foot** 95 dB - Low
105 dB - High
- Relay Contacts** Form C Dry 0-30 Volts
AC/DC, 1 Amp
- Dimensions** 5.375 in. x 5.375 in. x 2 in.
137mm x 137mm x 51mm
- Standby Current** 10 uA
- Alarm Current** 130mA at 95 dB / 200mA at 105 dB
- Recommended Operating Temperature** 32°F to 113°F
(0°C to 45°C)

APPROVALS & WARRANTY

- TESTING**
- STI-6400WIR & STI-6402WIR**
- FCC & IC Compliant (WIR versions only)
 - CE Approved

WARRANTY

Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

FEATURE	JP2	JP3	JP4	JP5	JP7
Volume - (105 dB) at 1 foot	ON*				
Volume - (95dB) at 1 foot	OFF				
Duration - 30 second alarm		OFF*	OFF*		
Duration - 180 second alarm		OFF	ON		
Duration - continuous alarm		ON	OFF		
Duration - annunciator mode		ON	ON		
Trip - immediate				OFF*	
Door prop mode				ON	
Arming - immediate					ON*
Arming - 15 second delay					OFF

*default