

**1443****VIP SYSTEM RELAY ACTUATOR MODULE**

Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in ViP system. Dimensions: 66X85X35mm (4 DIN modules).



1443

VIP SYSTEM RELAY ACTUATOR MODULE

COMPATIBLE SYSTEMS

ViP	Yes
-----	-----

ELECTRICAL CHARACTERISTICS

Type of power supply	PoE
Absorption (W)	Min 0,7 - Max 2,6
PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)

HARDWARE FEATURES

Number of outputs (n°)	2
Type of outputs	Open Collector, Relay (C-NO-NC, 10A@12÷24 VAC/VDC)
Number of digital inputs (n°)	2
Communication ports	RJ45 (Ethernet), RS485

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network	Ethernet 10 Mbit/s
---------------------	--------------------

GENERAL FEATURES

Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
Type of finishing materials	Plastic
Product color	White
Depth (inch) (in)	3.35
Height (inch) (in)	1.38
Width (inch) (in)	2.6

MAIN FEATURES

Operating temperature (°F)	14 ÷ 86
Operating humidity (RH max) (%)	25 ÷ 95
DIN rail mounted	Yes
DIN modules (no.) (n°)	4