

**EX-9000H****7" MAXI MONITOR. S2 SYSTEM FOR USA**

Maxi colour monitor for flush mounting (using optional box art. 6817) or surface mounting (with optional support art. 6820), with 7" / 16:9 touch screen, full-duplex hands-free audio and touch-sensitive commands. Allows brightness, contrast, audio volume and ringtone volume adjustment. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 6 programmable buttons for self activation, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position dip-switches for user code programming and button programming. Equipped with riser distribution terminal art. 1214/2C. The monitor can be used in 2-wire Simplebus2 systems. Dimensions (L x H x D): 223x124x25 mm.

**AWARDS**DESIGN  
MILANO



**EX-9000H**

**7" MAXI MONITOR. S2 SYSTEM FOR USA**

**GENERAL DATA**

Height (inch) (in)	4.88
Width (inch) (in)	8.78
Depth (inch) (in)	0.98
Product weight (oz) (oz)	22.93
Product color	White RAL9003, base grey RAL7001
Type of finishing materials	ABS, Glass
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory
Desk base-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888CU	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

**DISPLAY**

Display size (")	7
Aspect Ratio	16:9
Resolution (pixels)	800x480

**AUDIO FEATURES**

Microphone	4mm (Ø), Omnidirectional
Loudspeaker	80mm (Ø), 80 Ohm, 1W
Technologies implemented	Full-Duplex

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)



**EX-9000H**

**7" MAXI MONITOR. S2 SYSTEM FOR USA**

**ELECTRICAL CHARACTERISTICS**

Absorption in stand-by (W)	1
Maximum absorption (W)	11.2

**HARDWARE FEATURES**

Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy)
No. of programmable buttons for additional functions	4
Clamps	L L - + CFP1 CFP2 S+ S- In1 In2
Removable terminals	Yes
Number of inputs (n°)	2
Number of outputs (n°)	1

**SETTINGS**

Loudspeaker volume	Yes
Microphone volume	Yes
Ringtone volume	Yes
Screen brightness control	Yes
Screen contrast	Yes
Screen colour	Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP30
Operating temperature (°F)	41 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	III
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**GENERAL FEATURES**



**EX-9000H**

**7" MAXI MONITOR. S2 SYSTEM FOR USA**

Door opener	Yes
Automatic door opening on call (Doctor)	Yes
Silent mode (Privacy)	Yes
Self Activation	Yes
CPS call	Yes
Intercom calls	Yes
Call forwarding	Yes
Outside door call input	Yes
Customisable ringtone	Yes
Automatic answer (handsfree)	Yes
Sending alarm calls	Yes
Actuator control	Yes
Multiple address	Yes
Door open signaling	Yes



**EX-9000H**

## **7" MAXI MONITOR. S2 SYSTEM FOR USA**

### **ACCESSORIES**



**6820 S2 & VIP MAXI MONITOR WALL SUPPORT**

Wall support for Maxi monitor in ABS UV resistant. White RAL 9003 colour.