

**UT8020****IP (VIP) ULTRA AUDIO/VIDEO MODULE**

Audio/video module for Ultra entrance panel, IP (ViP) system. Twilight sensor for automatic nameplate backlighting power-off during daytime hours. Omnidirectional digital microphone and dual loudspeaker for high-fidelity audio. Wide-angle colour video camera (field of vision: 160° horizontal, 90° vertical) and LED for night-time lighting. Audio-visual indications for disabled individuals assistance request can be activated via programming. Facility for 2 call buttons. To be finished with a cap, single button or double button in professional-grade plastic given an anti-yellowing and anti-dulling treatment or in aluminium. Regulation and programming without removing the module. Dimensions: 1 Ultra module. ULTRA, the new and most technologically advanced entrance panel offering maximum ease of installation. Available in flush-mounted (10 mm protrusion from the wall) or surface-mounted (just 35 mm protrusion from the wall) variants. Dimensions: 100x90x35 mm.

AWARDSDESIGN
MILANO



UT8020

IP (VIP) ULTRA AUDIO/VIDEO MODULE

GENERAL DATA

| | |
|-----------------------------|---------------------------------------|
| Type | Modular |
| Height (inch) (in) | 3.54 |
| Width (inch) (in) | 3.94 |
| Depth (inch) (in) | 1.38 |
| Product weight (oz) (oz) | 13.93 |
| Product color | Aluminium, Black RAL9005, Transparent |
| Type of finishing materials | Polycarbonate, Aluminium alloy |
| Flush-mounted | Yes, with a dedicated accessory |
| Wall-mounted | Yes, with a dedicated accessory |

COMPATIBLE SYSTEMS

| | |
|------------|-----|
| Vip system | Yes |
|------------|-----|

AUDIO FEATURES

| | |
|--------------------------|--|
| Microphone | MEMS audio digital sensor, omnidirectional |
| Loudspeaker | 28mm (Ø), 8 Ohm, 1W (2) |
| Technologies implemented | Echo canceling, Noise reduction |
| Audio compression | G.711 A-Law |

CAMERA FEATURES

| | |
|--------------------------------|-------------------------------------|
| Camera | Colors |
| Sensor type | 1/2.7" CMOS - 2MP |
| Lens optical dimensions (in) | 0.06 |
| Angle of view (H x V - °) | 160 x 90 |
| Sensitivity | 0.1 (color) |
| Video resolution | 320x240, 480x272, 800x480, 1024x608 |
| Video compression | H.264 baseline |
| RTSP server | Yes |
| Maximum number of RTSP clients | 4 |



UT8020

IP (VIP) ULTRA AUDIO/VIDEO MODULE

CAMERA FEATURES

| | |
|------------------|-------------------------------------|
| RTSP resolutions | 1024x608, 800x480, 480x272, 320x240 |
|------------------|-------------------------------------|

ELECTRICAL CHARACTERISTICS

| | |
|----------------------------|---|
| Type of power supply | PoE, External power supply |
| Supply voltage | 33VDC |
| PoE power supply | 36÷57VDC, standard PoE, Comelit PoE (56VDC) |
| PoE class | Class 0 |
| Absorption in stand-by (W) | 2.5 |
| Maximum absorption (W) | 6 |

HARDWARE FEATURES

| | |
|-----------------------------|---|
| Call type | Push-buttons |
| Type of buttons | Mechanical |
| Number of push-buttons (n°) | 2 |
| Backlight color | White, Off |
| Clamps | TX- TX+ RX- RX+ V- V+ RTE GND/SE- SE+ COM NC NO |
| Number of inputs (n°) | 1 |
| Number of outputs (n°) | 2 |
| Type of outputs | Relay (C-NO-NC, 4A@12÷24 VAC/VDC, 10A peak), SE: unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum impedance 18 Ohm) |
| Communication ports | Ethernet |
| Twilight sensor | Yes |

SETTINGS

| | |
|----------------------|-----|
| Loudspeaker volume | Yes |
| Microphone volume | Yes |
| Backlight brightness | Yes |
| Recording area | Yes |



UT8020

IP (VIP) ULTRA AUDIO/VIDEO MODULE

NETWORK AND COMMUNICATION PROTOCOLS

| | |
|-----------------------|-----------------------------------|
| Type of LAN network | Ethernet 10 Mbit/s |
| IP address assignment | Auto IP, DHCP, Static |
| Protocols supported | DHCP, IPv4, NTP, RTSP, DNS, MQTTS |

PROGRAMMING MODE

| | |
|----------------------|-----|
| ViP Manager software | Yes |
|----------------------|-----|

ENVIRONMENTAL AND COMPLIANCE FEATURES

| | |
|-----------------------------------|--|
| IP protection rating | IP65 |
| Vandal Resistant rating (IK code) | IK08 |
| Operating temperature (°F) | -13 ÷ 131 |
| Operating humidity (RH max) (%) | 25 ÷ 95 |
| Environmental class | IV |
| Certifications | RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011) |

MAIN FUNCTIONS

| | |
|-------------------------------------|-----|
| Door opener | Yes |
| Number of auxiliary relays (n°) | 1 |
| Input for local door release button | Yes |
| Door open signaling input | Yes |
| Visual indications of system status | Yes |
| Acoustic signals of system status | Yes |
| Speech synthesis of system status | Yes |



UT8020

IP (VIP) ULTRA AUDIO/VIDEO MODULE

ACCESSORIES



UT9171 WALL HOUSING FOR 1 ULTRA MODULE

Surface-mounted housing, 1 module, for Ultra entrance panel. It consists of a metal support that secures the modules without using screws and a finishing frame in die-cast aluminium given a cataphoresis treatment to increase its resistance to chemical and environmental corrosion, including damage from UV rays. Just 35 mm protrusion from the wall. Dimensions: 110x107x35mm