

OVERVIEW

The P620 is a mullion mount 125 kHz wiegand proximity and keypad reader. Up to 5" non-contact read range with clamshell card. Can read Hartmann 40 bit credentials, certain HID®, AWID® and Pyramid credentials.





SPECIFICATIONS

DIMENSIONS

Mullion mount: 6.1" x 1.78" x 0.91"
Weight: 113g.

VOLTAGE INPUT

5-14 VDC

CURRENT DRAW

50mA typical, 115 mA peak.

OPERATING TEMPERATURE

-40°F to +149°F (-40°C to +65°C)
Outdoor/Indoor rated.

INTERFACE

Wiegand 12" pigtail included.

Wire spec 152m (500') Max Distance, 6 conductors stranded 24, overall foil shielded.

FREQUENCY

125 kHz

CREDENTIAL COMPATIBILITY

Hartmann 40 bit, certain HID®, AWID® and Pyramid credentials.

KEYPAD

12-PIN keypad label is made of durable polyester material. 8 bit burst output or wiegand. Illuminated.

READ RANGE

PSC1 - up to 5 inches, PSI4 - up to 3 inches, PSK3 - up to 3 inches.

CERTIFICATIONS

FCC, ICC, CE, C-Tick, UL Standard 294.



P620

Mullion Mount Combination Keypad and Proximity Reader

SPECIFICATIONS

MISC

Four state LED indicator (red, green, amber, off)
Built in buzzer. May be mounted directly to metal.

RELATED PART NUMBERS

PROX3

Mullion/single gang combo proximity reader. Reads 125 kHz HID/AWID/Hartmann credentials. Up to 6" read range. Indoor/ Outdoor. Wiegand compatible.

P640

Single gang combination keypad and proximity reader. Reads 125 kHz HID/AWID/Hartmann credentials. Up to 6" read range. Indoor/Outdoor. Wiegand compatible.

P620

Mullion mount combination keypad and proximity reader. Reads 125 kHz HID/AWID/Hartmann credentials. Up to 6" read range. Indoor/Outdoor. Wiegand compatible.

P710

Medium range proximity reader. Reads 125 kHz HID/AWID/Hartmann credentials. Up to 15" read range. Indoor/Outdoor. Wiegand compatible. Linear 12VDC Power supply recommended.

P900

Long Range Proximity reader. Reads 125 kHz HID/AWID/Hartmann credentials. Up to 20" Read range. Indoor/Outdoor. Wiegand compatible. Linear 12DC power supply recommended.