

OVERVIEW

The PSC1 is a standard ABS clamshell proximity credentials. Pre-programmed with site code card number (printed on card) formatted as Hartmann 40 bit. Operates at 125 kHz. Up to 6" of range.



SPECIFICATIONS

DIMENSIONS

3.4" x 2.2" x 0.06" Weight: 9g

OPERATING TEMPERATURE

-35°F to +122°F (-37°C to +50°C)

FREQUENCY

125 kHz

CARD FORMAT

Hartmann 40 bit



SPECIFICATIONS

READ RANGE

Up to 6 inches (152mm)

MATERIAL

ABS, off-white

MARKING

Site code, Card Number, Format Code

SLOT PUNCH

Standard, vertical slot

COMPATIBILITY

Meant for use with any of the following part numbers:

PROX3 P640 P620 P710 P900 P403/405 P453/P455



PART NUMBERS

PSC1

Proximity card clamshell ABS 125 kHz Hartmann 40 bit format.

PSK3

Proximity key tag fob 125 kHz. Hartmann 40 bit format.

PSI4

Proximity card PVC 125 kHz graphic quality printable dual-side (46mil) Hartmann 40 bit format.

PSM-2P

Proximity card PVC 125 kHz graphic quality printable dual-side (31mil) Hartmann 40 bit format.

PDT-1

Proximity disk tag with adhesive backed PVC 125 kHz. Hartmann 40 bit format.