

# **POE-APERIO-8**

PoE Powered ASSA ABLOY Aperio Access Controller

# **OVERVIEW**

The POE-APERIO-8 is a special door controller that communicates with up to 8 ASSA ABLOY APERIO wireless locksets. This controller has a RS485 module that connects to one or more Aperio AH30R12 (1:8, RS485 flavor firmware) wireless hubs. Must be Aperio certified by ASSA ABLOY in order to install. Supports A100, IN100, K100, K5100 locksets.



# POWER OVER ETHERNET

Only pull a single CAT5 cable to the controller to provide both power and communication.



#### **ONBOARD DIAGNOSTICS**

Using the LCD display and buttons on the controller, reader, output and input issues can be troubleshot. Diagnostics and IP programing also accessible via password protected web interface.



#### **SOLID STATE DESIGN**

Our solid state designed controllers have no moving parts to ensure reliability.



#### **APERIO**

Up to 8 Aperio Wireless Locksets can be connected through 1 or more AH30R12. Compatible locksets include: Supported: A100, IN100, PR100, K100, K5100.

# **SPECIFICATIONS**

### **ENCLOSURE**

Black ABS enclosure,  $10^{\circ}$  x  $2.2^{\circ}$  x  $3.5^{\circ}$ . Includes mounting screws and wall anchors. Optional backbox available (ODM-BACKBOX) with  $6 \times 3/4^{\circ}$  conduit knockouts for concrete or brick walls.

# COMMUNICATION

1 x RJ-45 10/100Mbps ethernet port, PoE standard (15.4W), 100m (328') max distance. **Wire Spec** 100m (328') Max Distance. Cat5 or better.

1 x RS485 port

Wire Spec 600m (2000') max distance, 2 conductor stranded, twisted pair 22 AWG, shielded.

# **OUTPUTS**

1 x 12V Out 12V @ 300mA

Wire Spec 152m (500') Max Distance, 2 conductors stranded 22 AWG.

**POE-APERIO-8** 



PoE Powered ASSA ABLOY Aperio Access Controller

# **SPECIFICATIONS**

#### **STORAGE**

Stores up to 100,000 cardholders. Stores up to 50,000 events, first in first out queue.

# **CERTIFICATIONS**

UL 294/ULC S319-05 listed, FCC

# **MISC**

Super capacitor maintains data and time up to 1 month without power. Photo-resistive tamper sensor. Piezo buzzer. Automatic DST switch.

# **SOFTWARE**

Door controller is programmed and monitored from PROTECTOR.Net server software. Software can be hosted by security integrator or via local/remote Windows PC/Server.

# WARRANTY

3 year warranty

# **ASSA ABLOY APERIO INTEGRATION**





