

DESCRIPTION

18 AWG 2 Conductor Stranded Bare Copper, Shielded with an overall jacket. 500 ft, Pull Box, White

APPLICATION

- Intercom Systems
- **Security Systems**
- **Sound and Audio**
- **Power Limited Control Circuits**
- **Indoor Applications**
- **Door Controllers**
- **Kev Pads**
- **Smoke Detectors**



ALARM-SECURITY CABLE

18 AWG 2 CONDUCTOR STRANDED CABLE (SHIELDED)

211-182ST/S/5WH

CONSTRUCTION

Conductor count: 2

Round Shape: Rip cord: Yes PE Tape: Yes Drain Wire (TC): 7/0.20 Aluminum Foil: Yes

CONDUCTORS

Material: Stranded bare copper

Trade size: **18 AWG** Stranding: 16/0.24 mm

0.02 in (0.47 mm) Strand Diameter:

Polyvinyl Chloride (PVC) Insulation material:

Insulation O.D.: 0.07 in. (1.7 mm) Insulation color: Red. Black

JACKET

Material: Polyvinyl Chloride (PVC)

Thickness: 0.02 in. (0.5 mm) O.D.: 0.17 in. (4.6 mm) Marking: Vertical 5024318 c(ETL)us CM/CL2

> 18AWG 2C STRANDED SHIELDED 75C SUN RES RoHS 19711N0406207 XXXXFT

MECHANICAL


Temperature rating: 75° C

SAFETY

Voltage rating: 300 V RMS

PACKED WEIGHT

211-182ST/S/5WH: 12 lb







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida

845.391.8318 New York

713.322.7242 Texas

www.verticalcable.com