


Product Data Sheet

☎ 1-888-452-HANA (4262) ✉ info@hanawireless.com



Model: HW2-N20R-R1F

16x20x15 Inch Weatherproof Enclosure with 120 Vac Mounting Plate, 4U Rack Mount
Thermostat Controlled Cooling System



Features

- Molded Fiberglass Reinforced Polyester (FRP)
- Stainless steel quick-release latches with padlock hasps
- NEMA Type 3R, 3RX / IP24 rated, fully gasketed lid
- 4U 19-inch rack mounting brackets
- Aluminum mounting plate with 120 Vac outlets, thermostat-controlled fan, patented (US8014157) slotted accessory mounting design

Applications


- Remote wireless LAN Wi-Fi equipment installations
- Indoor and outdoor installations
- Rapid deployment and hotspot installations
- Harsh and corrosive environments
- Protection of equipment from theft and damage

Specifications

Material	FRP
Color	Tool Gray – RAL 7035
Voltage Vac	120
Heater F° (C°)	N/A
Heat Temperature ON/OFF F° (C°)	N/A
Fan Power Watt	24
Fan Temperature ON/OFF F° (C°)	100 (38) +/-3 / 70 (21) +/-5
Mounting Plate Dimensions in (mm)	7.1 (180) x 18.8 (478) x 0.1 (2.5)
Mounting Plate Material	Anodized Aluminum
Weight lb (kg)	25.8 (11.7)
Outside Dimensions, Max in (mm)	17.3 (440) x 21.3 (541) x 15.6 (396)
Inside Dimensions in (mm)	15.7 (399) x 19.7 (500) x 15.1 (384)
Flame Rating	UL 94-5V
RoHS	Compliant
Environmental Rating NEMA - IP	3R, 3RX - 24
Cable Feed	1/2in Conduit Connector

Package Specifications

Package Quantity	1 per Carton
Length in (mm)	23.0 (584)
Width in (mm)	19.5 (495)
Depth in (mm)	19.5 (495)
Weight lb (kg)	26.3 (11.9)



Wireless That Works