

Product Data Sheet

☎ 1-888-452-HANA (4262) ✉ info@hanawireless.com

Model: HW2-N30-R1F

30x24x11 Inch Weatherproof Enclosure with 120 Vac Mounting Plate, 5U Rack Mount, Thermostat-Controlled Cooling System

Features

- Molded Fiberglass Reinforced Polyester (FRP)
- Stainless steel quick-release latches with padlock hasps
- NEMA Type 3R, 3RX / IP24 rated, fully gasketed lid
- 5U 19-inch sliding rack mounting brackets
- Aluminum mounting plate with 120 Vac outlets, thermostat-controlled fan, patented (US8014157) slotted accessory mounting design

Applications

- Remote wireless LAN Wi-Fi equipment installations
- Indoor and outdoor installations
- Rapid deployment and hotspot installations
- Harsh and corrosive environments
- Protection of equipment from theft and damage



Specifications

Material	FRP
Color	Tool Gray – RAL 7035
Voltage Vac	120
Heater F° (C°)	N/A
Heat Temperature ON/OFF F° (C°)	N/A
Fan Power Watt	24
Fan Temperature ON/OFF F° (C°)	100 (38) +/-3 / 70 (21) +/-5
Mounting Plate Dimensions in (mm)	23.3 (592) x 15.3 (389) x 0.1 (2.5)
Mounting Plate Material	Anodized Aluminum
Weight lb (kg)	31.0 (14.1)
Outside Dimensions, Max in (mm)	31.5 (800) x 25.5 (648) x 13.5 (343)
Inside Dimensions in (mm)	30.0 (762) x 24.0 (610) x 10.6 (269)
Flame Rating	UL 94-5V
RoHS	Compliant
Environmental Rating NEMA - IP	3R, 3RX - 24
Cable Feed	1x 1/2in Conduit 4x PG11

Package Specifications

Package Quantity	1 per Carton
Length in (mm)	0.0 (000)
Width in (mm)	0.0 (000)
Depth in (mm)	0.0 (000)
Weight lb (kg)	51.4 (23.3)

Wireless That Works