

VERTICAL CABLE


Simply Connect.

DESCRIPTION

Category 5E V-Max Keystone Jack **Unshielded - TAA-Compliant Lifetime Warranty**

FEATURES

- Color Coded for T568A and T568B standards
- Meets and Exceeds ANSI/TIA-568-C.2, **ANSI/TIA 1096-A**
- Supports PoE 802.3af, 802.3at, 802.3bt
- Meets and Exceeds ANSI/TIA-568-C.2
- · Fits most standard keystone wall plates and patch panels
- · Narrow connector allows high port density in small areas
- Compatible with standard 110 punch down tool
- Use the V-Max I-Punch Tool for faster termination
- Available in various colors for easy Identification
- UL Listed, RoHS Compliant, TAA Compliant
- Available in x25 Packs



VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

CATSE UNSHIELDED KEYSTONE JACK (V-MAX Series)

351 Series

Height	Width	Depth	Weight (Single Jack)	Weight (25 Pack)
0.78 in.	0.67 in.	1.22 in.	0.04 LB	0.5 LB

SPECIFICATIONS

RJ45 JACK

Housing Material: ABS+PC UL 94V-0

Contact Bracket: PBT+Glass Fiber, UL 94V-0

RJ45 JACK CONTACT

Phospor Bronze with Nickel plating Material:

Finish: 50 μ" Gold plating on Plug

contact area

IDC

Housing: PC UL 94V-0 with Black color Terminal: Phosper Bronze with Tin plating

Cap: ABS+PC UL 94V-0 FR4. UL 94V-0 PCB:

PERFORMANCE

Color Code: T568A & T568B wiring Insertion Force: 20N max. (IEC 606037-3)

Retention Force: 17 lb (7.7 kg) between jack and plug

Operating Temp.: -10° C to 60° C max

(ISO/IEC 11801, ANSI/TIA 568 C.2)

OPERATING LIFE (MATING CYCLES)

Min. 750 cycles Jack:

(ISO/IEC 11801, IEC 60603-7-3)

IDC: Suitable for 23 and 24 AWG solid wire

COLORS AVAILABLE

Black, Blue, Grey, Green, Ivery, Yellow, Red, White, Orange, Purple














verticalcable.com

















VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

verticalcable.com