

VERTICAL CABLE

Simply Connect.

DESCRIPTION

Category 6 V-Max Keystone Jack **Unshielded - TAA-Compliant Lifetime Warranty**

FEATURES

- Color Coded for T568A and T568B standards
- Meets and Exceeds ANSI/TIA-568-C.2. **ANSI/TIA 1096-A**
- Supports PoE 802.3af, 802.3at, 802.3bt
- Meets and Exceeds ANSI/TIA-568-C.2
- Fits most standard keystone wall plates and patch panels
- · Narrow connector allows high port density in
- Compatible with standard 110 punch down tool
- Use the V-Max I-Punch Tool for faster termination
- Available in various colors for easy Identification
- UL Listed, RoHS Compliant, TAA Compliant
- Available in x25 Packs (Check for Availabilty)



VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas

CAT6 UNSHIELDED KEYSTONE JACK (V-MAX Series)

352 Series

Height	Width	Depth	Weight (Single Jack)	Weight (25 Pack)
0.78 in.	0.67 in.	1.22 in.	0.04 LB	0.5 LB

SPECIFICATIONS

RJ45 JACK

Housing Material: ABS+PC UL 94V-0

Contact Bracket: PBT+Glass Fiber, UL 94V-0

RJ45 JACK CONTACT

Phospor Bronze with Nickel plating Material:

Finish: 50 μ" Gold plating on Plug

contact area

IDC

PC UL 94V-0 with Black color Housing: Terminal: Phosper Bronze with Tin plating

ABS+PC UL 94V-0 Cap: FR4. UL 94V-0 PCB:

PERFORMANCE

Color Code: T568A & T568B wiring Insertion Force: 20N max. (IEC 606037-4)

Retention Force: 17 lb (7.7 kg) between jack and plug

-10° C to 60° C max Operating Temp.:

(ISO/IEC 11801, ANSI/TIA 568 C.2)

OPERATING LIFE (MATING CYCLES)

Min. 750 cycles Jack:

(ISO/IEC 11801, IEC 60603-7-4)

IDC: Suitable for 23 and 24 AWG solid wire

COLORS AVAILABLE

Black, Blue, Bright White, Green, Grey, Ivory, Orange, Purple, Red, White, Yellow














verticalcable.com























VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York 713.322.7242 Texas