

and an autoresponder. OS - Linux.

Specifications

7" TFT LCD (capacitive touchscreen) Display

Screen resolution 800 x 480

Built-in camera

PoE and + 12 V DC (PSU not included) Power

Power consumption 6 W, standby 2.5 W

Dimensions 195 x 127 x 27 mm Colors Black / White Plastic Body

Installation Type Wall mount

Mounting options Horizontal and vertical

Possibilities of connection

Number of individual

panels

Number of multi-

apartment panels

Connection of additional monitors

Memory function Interface

Number of IP cameras

Up to 9 panels

Up to 9 panels

Up to 8 monitors

Record photo into internal memory (64 photo) Multi-language graphical and WEB interface

Up to 8 cameras

Main features

7" TFT display with capacitive touch



Record photo to internal memory



Screen Resolution 800×480



Support of receiving messages



Individual panels: up to 9 panels



Do Not Disturb mode



Multi-apartment panels: up to 9 panels



Silent mode



IP cameras: up to 8 cameras



Connection of the door bell



PoE and +12V DC



Horizontal and vertical mounting options

Functional capabilities

Intercom type Audio Intercom (no built-in camera)

Support of receiving messages Y

Yes

Select the type of screensaver

in standby mode

Single IP camera live viewing


Do Not Disturb Silent mode Yes, customizable by time Yes

Software update

From the web interface From BAS-IP updates server

Color variations





Appearance and mechanical mounting

