Akuvox S563 Datasheet

Premium Indoor Monitor for Your Home

The Akuvox S563 is an 8-inch SIP indoor monitor that runs on the Android 12 operating system. It features an exceptional speaker and a high-resolution touchscreen display, ensuring an unparalleled audio-visual intercom experience. Its stylish and space-saving design blends seamlessly into modern homes.

3:40 AM | 21° | 2000 00333 - Wed | 2 ° | 2000 0033 - Wed | 2 ° | 2000 0033 - Wed | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2 ° | 2

At a Glance

- Seamless compatibility with Android 12 OS
- Exceptional two-way audio communication
- Easy integration with SIP PBXes
- Powered by PoE or an external power supply
- Voice changer function to protect vulnerable individuals
- Compatible with US or European electrical wall boxes
- Built-in smart voice assistant

Physical & Power

• Front panel: Plastic

• RAM / ROM: 2GB / 8GB

• Display: 8 Inch IPS LCD

• Screen: 8 Inch capacitive touch screen

• RS485 Port: Support

• Relays Out: 1

• Bell in: 1

• Alarm Input: 8

• Microphone: one microphones, -26dB

• Speaker: one speakers, 4Ω / 2W

• Ethernet Ports: 2xRJ45, 10/100Mbps adaptive

• 802.3af Power-over-Ethernet

• 12V DC Connector (if not using PoE)

• Tamper Resistant: Support

• Installation: Wall-mounted & Desktop

• Dimension: 216.2x124.4x22.1 mm

Working Humidity: 10~90%

• Working Temperature: -10°C ~ +45°C

• Storage Temperature: -20°C ~ +70°C

Akuvox S563 Datasheet

Touch Screen Display

• Display Mode: Normally black, Transmissive

• LCD Size: 8 inch (Diagonal)

Aspect Ratio: 16:10

• Resolution: 1280x800

• Contrast ratio: 1200:1

• Luminance: 310 cd/m²

• Viewing Angle: 80° Left, 80° Right,

80° Upper, 80° Lower

• Touch Screen: Projected capacitive

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ, G.729
- Broadband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833),
 SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator
- Automatic Gain Control

Video

• Streaming formats: H.263 & H.264

Networking

Protocols support: IPv4, HTTP, HTTPS, FTP, TFTP,
 SNMP, DNS, SNTP, RTSP, SRTP, RTP, TCP, UDP,
 TLS, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Firmware upgrade
- System logs (include door access logs)

Voice Assistant

- Voice pickup distance up to 5 meters
- Voice recognition accuracy up to 95%
- Privacy protection with native voice data
- Support English

Application Scenario

- Villas
- Apartment complexes
- Home automation systems
- Modern interiors

