



## 7" Touchscreen for M1 & E27 Controls

### ELK-7TS

The ELK-7TS Touchscreen is a sleek, Wi-Fi-enabled 7-inch interface designed for seamless control of ELK security and automation systems. Its vibrant high-resolution display ensures an intuitive user experience with responsive touch controls. Installers can easily select between two tailored interfaces during setup: a modern M1 touchscreen application for M1 systems and a touchscreen version of ElkConnect for E27 Alarm Engine installations.\*

### Features/Specifications

- 7" HD Display (1024 x 600 Resolution)
- Ultra Low Profile screen with slim wall mount plate
- Responsive capacitive touchscreen, with 5-point multi-touch
- G+G Gorilla Glass screen
- Wi-Fi connectivity (802.11b/g/n 2.4GHz)
- Power: 12VDC, 1A (power supply not included, ELK-P1417 recommended)
- Size: 7.59" x 4.56" x 0.56"



**ELK-DS47TS**  
Optional Desk Stand



**ELK-POE47TS**  
Optional Ethernet/PoE Adapter

\*Estimated release for E27 Support late Q1 2025



***Solutions for Serious Security and Automation Professionals***

(800) 797-9355 | [www.elkproducts.com](http://www.elkproducts.com)

# Desk Stand for ELK-7TS Touchscreen

## ELK-DS47TS

The ELK-DS47TS is a sleek, versatile stand designed for mounting the ELK-7TS touchscreen on desks, tables, or countertops. Its pre-drilled holes align perfectly with the ELK-7TS backplate for a secure fit.



A large cable access hole simplifies wiring, while the wedge design provides excellent cable management and space for the optional ELK-POE47TS Ethernet/PoE adapter.

### Features/Benefits

- Pre-drilled holes for mounting back plate
- Large cable access hole
- Ample space for installing optional ELK-POE47TS Ethernet/PoE adapter
- Anti-slip foam strips on feet of stand

### Key Specifications

- Size: 6.45" x 5.75" x 3"
- Color: White
- Includes 4) self-tapping mounting screws, 2) adhesive cable tie mounts, and 2) cable ties

# Ethernet & PoE Adapter for ELK-7TS Touchscreen

## ELK-POE47TS

The ELK-POE47TS is an Ethernet and PoE adapter for the ELK-7TS touchscreen, offering two key functions:



- Ethernet Adapter: Connects the ELK-7TS to a network via a patch cable when Wi-Fi is unavailable or undesired. In this setup, a separate 12VDC power source is required for the touchscreen.
- PoE Adapter: Provides both power and network connectivity when paired with a PoE-enabled switch or injector, with power supplied by the PoE device.

### Features/Benefits

- RJ45 port and pre-wired touchscreen connector for easy installation
- Network processor and traffic LEDs indicators
- 15" cable to touchscreen

### Key Specifications

- LAN Bandwidth: 10/100 Mbps
- Supported PoE standard: 802.11at
- Required PoE Power Input: 24VDC - 57 VDC
- Power Output (when used with PoE switch or injector): 12VDC, 1.5A