

## HS-1500WT

### SPEAKER SYSTEM



One of the most difficult speaker requirements to satisfy is a cost-effective mid-size speaker system that offers high quality sound no matter what the application. TOA HS-Series speakers are equipped with narrow-directivity control (90° horizontal × 40° vertical). This useful feature allows tailoring the speaker's dispersion characteristics to better suit the acoustic environment in which it is installed. The versatile HS-Series is compatible for use with 100V/70V lines for distributed applications. The HS-Series speakers are exceptional in offering useful features at an attractive price.


### Key features

- 15" LF speaker
- Well-controlled sound coverage: 90° horizontal x 40° vertical
- High impedance version
- Easy to carry and easy to install, with handle for easy transportability
- Twin input terminal connections (Speakon® and screw terminals) for fixed and mobile installation
- Size and weight have been reduced thanks to the use of the array tweeter
- Can be used as a floor monitor


## Specifications

Enclosure	Sealed type
Rated Input	60 W (High Impedance)
Power Handling	Continuous pink noise: 100 W (Low Impedance) Continuous program: 300 W (Low Impedance)
Rated Impedance	8 $\Omega$ 100 V line: 170 $\Omega$ (60 W), 330 $\Omega$ (30 W), 670 $\Omega$ (15 W) 70 V line: 83 $\Omega$ (60 W), 170 $\Omega$ (30 W), 330 $\Omega$ (15 W), 670 $\Omega$ (7.5 W)
Sensitivity	98 dB (1 W, 1 m)
Frequency Response	60 - 20,000 Hz
Crossover Frequency	3 kHz
Directivity Angle	Horizontal: 90°, Vertical: 40°
Speaker Component	Low frequency: 38 cm (15) cone-type
Input Terminal	NEUTRIK NL4MPXX Speakon and M4 screw terminal, distance between barriers: 9 mm (0.35")
Operating Temperature	-10# to +50# (14# to 122#)
Finish	Enclosure: Polypropylene, white Punched net: Surface-treated steel plate, white
Dimensions	451 (W) x 560 (H) x 400 (D) mm (17.76 x 22.05" x 15.75")
Weight	14 kg (30.86 lb)
Included Accessories	Handle ...1, Handle fitting bracket ...2, Handle mounting screw ...2, Rubber foot ...2, Rubber foot mounting screw ...2
Optional Accessories	Mounting bracket: HY-1500VW (for vertical speaker mounting) HY-1500HW (for horizontal speaker mounting) Ceiling mount bracket: HY-C0801W, Wall mount bracket: HY-W0801W Speaker stand: ST-33B


## Dimensions




Front View



Side View



Rear View



Bottom View






Figure of the unit installed



ST-34B (option) mounting

UNIT:mm

## A&E specifications

The speaker shall be the two-way speaker with a sealed box enclosure with polypropylene and a protective punched front grill with a surface-treated steel plate. The speaker shall be compatible with low and high impedance speaker systems and include a built-in 100V matching transformer. The rear panel shall have screwdriver-adjustable tap settings of: 60W, 30W, 15W and 8 ohms. The rated input shall be 60W, the continuous pink noise shall be 100W at 8 ohms and continuous program shall be 300W at 8 ohms. The speaker shall feature a 38 cm (15") woofer and a 6-balanced-dome tweeters array with a 90° x 40° dispersion. Frequency response shall be 60 to 20k Hz, with crossover at 3k Hz. Sensitivity shall be rated at 98 dB (1 W, 1 m). The speaker system shall be designed for both fixed installation uses and on-the-road and shall be capable of being easily carried with an accessory handle. Its built-in overload protection circuitry for tweeter shall cut off a signal when an excessive input signal is received. Input connections shall be via a speakon connector or screw terminal.

The speaker system shall weigh 14 kg and shall have dimensions of 451(W) x 560(H) x 400(D) mm. The operating temperature range shall be between -10°C and +50°C. The speakers shall be easily mounted in vertical or horizontal positions, with a wide range of optional brackets.

The two-way speaker system shall be a TOA model HS-1500BT/HS-1500WT or approved equivalent.

The wall/ceiling-mount bracket shall be TOA model HY-1500HB/HY-1500HW/HY-1500VB/HY-1500VW.

The ceiling-mount bracket used in conjunction with HY-1500HB/HY-1500HW/HY-1500VB/HY-1500VW shall be TOA model HY-C0801/HY-C0801W.

The wall-mount bracket used in conjunction with HY-1500HB/HY-1500HW/HY-1500VB/HY-1500VW shall be TOA model HY-W0801/HY-W0801W.