

Specification	
Part No.	CLHDS-1X2
Technical	
Input	HDMI×1
Output	HDMI×2
Input cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Output cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Video support	480i@60Hz、480p@60Hz、576i@50Hz、576p@50Hz、 720p@50/60Hz、1080i@50/60Hz、1080p@50/60Hz、4K×2K@24/25/30/60Hz
HDR	Support
Audio format	Support standard audio and DSD (Direct Stream Digital) and HD(HBR) audio
TMDS signal	0.5～1.5Vp-p(TMDS)
DDC signal	5Vp-p(TTL)
EDID DIP Switch	YES
HDCP	HDCP2.2, HDCP1.4
Mechanical	
Housing	Iron
Dimensions(L×W×H mm)	96×59×16.8mm
Net weight	100g
Power supply	5V/1A
Power consumption	<3W
Operation temperaure	0~60°
Storage temperature	—20~70°
Relative humidity	20-90% (no condensation)



- Distributes 1 HDMI Source to 2 HDMI displays
- Supports ultra HD resolution 4Kx2K@60Hz

- Supports HDMI 3D
- Includes EDID function
- Supports HDR

- Low Power Consumption
- Plug and Play

*The terms, interfaces and logos related to "HDMI" are intellectual properties of HDMI Licensing Administration, Inc.