

Specification	
Part No.	CLHDS-1X4
Technical	
Input	HDMI×1
Output	HDMI×4
Input cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Output cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Video support	480i@60Hz、480p@60Hz、 576i@50Hz、576p@50Hz、 720p@50/60Hz、1080i@50/60Hz、 1080p@50/60Hz、4K×2K@24/25/30/60Hz
HDR	Support
Audio format	Support standard audio and DSD (Direct Stream Digital) and HD(HBR) audio
TMDS signal	0.5~1.5Vp-p(TMDS)
DDC signal	5Vp-p(TTL)
EDID DIP Switch	YES
HDCP	HDCP2.2, HDCP1.4
Mechanical	
Housing	Iron
Dimensions(L×W×H mm)	158×80×17mm
Net weight	200g
Power supply	5V/1A
Power consumption	<3W
Operation temperaure	0~60°
Storage temperature	—20~70°
Relative humidity	20-90% (no condensation)

8313252563124



Insert SN here



HDMI

HIGH DEFINITION MULTIMEDIA INTERFACE

LIGHTNING FAST

4K HDMI SPLITTER

CLHDS-1X4



- Distributes 1 HDMI source to 4 HDMI displays
- Ultra HD resolution 4Kx2K@60Hz

- Supports HDMI 3D
- Includes EDID function
- Supports HDR

- Low Power Consumption
- Plug and Play

*The terms, interfaces and logos related to "HDMI" are intellectual properties of HDMI Licensing Administration, Inc.

170.00 mm

150.00 mm