

Specification

Part No.	CLIFE-KIT / Receiver CLIFE-RX	
Technical	Transmitter	Receiver
HDMI compliance	HDMI1.4	
HDCP compliance	HDCP1.4	
Resolution	480i@60Hz、480p@60Hz、576i@50Hz、576p@50Hz、 720p@50/60Hz、1080i@50/60Hz、1080p@50/60Hz、4Kx2K @24/25/30Hz	
Network Cable	UTP/STP Cat5/5e/6	
Transmission distance	Up to 120m transmission distance for 4K×2K@30Hz Full HD over single CAT6	
PoE	support	
IR passback	Supports 20~60KHz IR devices	
Mechanical	Transmitter	Receiver
Material	Aluminum alloy	
Color	Black	
Dimensions(L×W×H mm)	107.3(W)×94(D)×23.7(H) mm	
Weight	TX: 275g	RX: 275g
Power supply	DC5V/2A	
Power consumption	4.5W	3.5W
Operation temperaure	0°C~60°C	
Protection	Lightning protection / Surge protection/ ESD protection	

8313252563123



Insert SN here



HDMI

HIGH DEFINITION MULTIMEDIA INTERFACE

LIGHTNING FAST

4K HDMI EXTENDER

CLIFE-KIT



- Plug and Play two network switch
- Receiver is powered by POE
- Extends HDMI signal up to 120 meters over single network cable
- Supports CAT5/5e/6 cables

- Supports up to 4Kx2K@30Hz
- IR extender
- Lightning Protection, Surge Protection, ESD Protection

- Only one transmitter needed for unlimited receivers
- Connects to network for HDMI splitter
- High-end aluminum alloy enclosure design

*The terms, interfaces and logos related to "HDMI" are intellectual properties of HDMI Licensing Administration, Inc.

170.00 mm

150.00 mm



