

## ProSeries Security and Life Safety Sensors

ProSiX is the next generation of the SiX® Two-Way Wireless Technology by Resideo for security and life safety. With its innovative technology and superior performance, ProSiX enables faster installation, easier troubleshooting, remote diagnostics and increased RMR. Its encrypted transmission ensures the highest level of data security.

Compatible with the ProSeries platform, ProSiX technology is available in a wide selection of devices used in intrusion, life safety, property protection, and wearable applications giving immediate and convenient access to important system functions.



## Features & Benefits

### Simple and Quick Install

- Speeds up installation and reduces errors with sensor's battery pull-tab, auto-enrollment and no-touch adjustment
- Reduces on-site visits with remote configuration

### Easy to Maintain

- Use System Health Check to proactively troubleshoot by monitoring device signal strength, sensor settings, and battery life anytime, anywhere

### Secure Encryption

- Employs 128-bit AES encryption for a high level of security

### Anti-Takeover

- Helps prevent competitive account takeovers and conversions since ProSiX devices are locked into panels and must be unpaired by the installing dealer to be used again

### One-Go-All-Go Interconnected Life Safety

- If one life safety device goes into alarm mode (Smoke/Heat/CO), all other associated life safety devices, including sirens, will sound to alert occupants

### Fewer Truck Rolls

- Reduces truck rolls with user-replaceable batteries and the ability to remotely adjust sensor parameters and download software updates

# FIRST ALERT® ProSeries Security and Life Safety Sensors

## Technical Specifications

### Intrusion Sensors

#### Door/Window Sensor



**PROSIXCTV (White) / PROSIXCTV-BR (Brown)**  
**Mounting Hardware:** Included  
**LED Indicators:** Yes  
**Magnet Spacing Gap\*:** ≤ 1.0 in (25.4 mm)  
**Auxiliary Input Terminal:** Yes  
**Typical Range\*:** 375 ft (114.3 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover and Wall  
**Power Requirements:** 3 V CR123A Lithium Battery, Qty 1 (Panasonic CR123A, Duracell DL123A or Huiderei CR123A)  
**Operating Temperature:** 32°F to 122°F (0°C to 50°C)  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (H x W x L):**  
**Sensor:** 1.1 in x 1.6 in x 3.1 in (27.9 mm x 40.6 mm x 78.7 mm)  
**Magnet:** 0.6 in x 0.4 in x 1.4 in (15.2 mm x 10.2 mm x 35.6 mm)  
**Approval Listings:** FCC/IC, cETLus Listed, Conforms to UL 634, Certified to ULC/ORD-C634  
**Other Standards:** RoHS

#### Mini Door/Window Sensor



**PROSIXMINI3**  
**Mounting Hardware:** Included  
**LED Indicators:** Yes  
**Magnet Spacing Gap\*:** ≤ 1.0 in (25.4mm)  
**Auxiliary Input Terminal:** No  
**Typical Range\*:** 300 ft (92 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover and Wall  
**Recommended Batteries:** 3V EVE CR2, Panasonic CR2, Great Power CR2, Lisun CR2  
**Operating Temperature:** 32°F to 122°F (0°C to 50°C)  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (H x W x L):**  
**Sensor:** 0.9 in x 1.0 in x 3.1 in (22.5 mm x 26.6 mm x 79.1 mm)  
**Magnet:** 0.6 in x 0.4 in x 1.7 in (14.9 mm x 10.8 mm x 43.7 mm)  
**Approval Listings:** FCC/IC, ETL Listed to UL 634, cETLus Listed to ULC/ORD-C634  
**Other Standards:** RoHS

#### Mini Door/Window Sensor (Flat style)



**PROSIXMINI**  
**Mounting Hardware:** Included  
**LED Indicators:** Yes  
**Magnet Spacing Gap\*:** ≤ 1.0 in (25.4mm)  
**Auxiliary Input Terminal:** No  
**Typical Range\*:** 200 ft (61 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover and Wall  
**Power Requirements:** 3 V CR2450 Lithium Coin Cell Battery, Qty 1 (Duracell DL2450, Panasonic CR2450 or Energizer CR2450)  
**Operating Temperature:** 32°F to 122°F (0°C to 50°C)  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (H x W x L):**  
**Sensor:** 0.5 in x 1.3 in x 2.4 in (12.7 mm x 33.0 mm x 61.0 mm)  
**Magnet:** 0.4 in x 0.4 in x 1.5 in (10.2 mm x 10.2 mm x 38.1 mm)  
**Approval Listings:** FCC/IC, cETLus Listed, Conforms to UL 634, Certified to ULC/ORD-C634  
**Other Standards:** RoHS

#### Motion Detector



**PROSIXPIRV**  
**Mounting Hardware:** Included  
**Detection Pattern:** 40 ft x 56 ft (12 m x 17 m)  
**LED Indicators:** Yes  
**Temperature Compensation:** Yes  
**Typical Range\*:** 375 ft (114.3 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover  
**Power Requirements:** 3 V CR123A Lithium Battery, Qty 1 (Panasonic CR123A, Duracell DL123A or Huiderei CR123A)  
**Operating Temperature:** 32°F to 122°F (0°C to 50°C)  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (H x W x D):** 4.1 in x 2.4 in x 1.6 in (104.1 mm x 61.0 mm x 40.6 mm)  
**Approval Listings:** FCC/IC, cETLus Listed, Conforms to UL 639, Certified to ULC-S306-03  
**Other Standards:** SIA-PIR-01, RoHS  
**Pet Immunity:** Yes

\*Please refer to the installation guide for additional details.

\*Varies based on each installation due to environmental and/or other conditions.

# FIRST ALERT® ProSeries Security and Life Safety Sensors

## Technical Specifications

(continued)

### Intrusion Sensors (continued)

### Flood/Leak Detection

#### Shock Sensor



##### PROSIXSHOCK

**Mounting Hardware:** Included

**Shock Sensitivity:**

Multi-directional

**LED Indicators:** Yes

**Magnet Spacing Gapt:**

< 0.95 in (24.1 mm)

**Auxiliary Input Terminal:** Yes

**Typical Range\*:** 300 ft (92 m)

RF Frequency: 2.4 GHz

**Encryption:** 128-bit AES

**Tamper Protected:**

Cover and Wall

**Power Requirements:** 3 V

CR123A Lithium Battery, Qty 1

(Panasonic CR123A, Duracell DL123A or Huiderui CR123A)

**Operating Temperature:**

32°F to 122°F (0°C to 50°C)

**Relative Humidity:**

95 % max., non-condensing

**Dimensions (H x W x L):**

**Sensor:** 1.1 in x 1.6 in x 3.1 in (27.9 mm x 40.6 mm x 78.7 mm)

**Magnet:** 0.6 in x 0.4 in x 1.4 in (15.2 mm x 10.2 mm x 35.6 mm)

**Approval Listings:**

FCC/IC, cETLus Listed,

Conforms to UL 634, Certified to

ULC/ORD-C634, ULC-S306

**Other Standards:** RoHS

#### Temperature Sensor



##### PROSIXTEMP

**Mounting Hardware:** Included

**LED Indicators:** Yes

**2-Zone Trigger Temperature:**

Cold: below 45°F (7°C)/

Hot: above 95°F (35°C)

**Typical Range\*:** 300 ft (92 m)

RF Frequency: 2.4 GHz

**Encryption:** 128-bit AES

**Tamper Protected:**

Cover and Wall

**Power Requirements:** 3 V

CR123A Lithium Battery, Qty 1

(Panasonic CR123A, Duracell DL123A or Huiderui CR123A)

**Operating Temperature:**

32°F to 122°F (0°C to 50°C)

**Relative Humidity:**

95 % max., non-condensing

**Dimensions (H x W x L):**

1.1 in x 1.6 in x 3.1 in (27.9 mm x 40.6 mm x 78.7 mm)

**Approval Listings:**

FCC/IC, cETLus Listed,

Conforms to ANSI/UL 873 and

ANSI/UL 2017, Certified to

CAN/CSA STD C22.2 #205

**Other Standards:** RoHS

#### Glassbreak Detector



##### PROSIXGB

**Mounting Hardware:** Included

**Detection Typical Range:**

25 ft (7.6 m)

**LED Indicators:** Yes

**Typical Range\*:** 300 ft (92 m)

RF Frequency: 2.4 GHz

**Encryption:** 128-bit AES

**Tamper Protected:**

Cover and Wall

**Power Requirements:** 3 V

CR123A Lithium Battery, Qty 1

(Panasonic CR123A, Duracell DL123A or Huiderui CR123A)

**Operating Temperature:**

32°F to 122°F (0°C to 50°C)

**Relative Humidity:**

95 % max., non-condensing

**Dimensions (Dia x D):**

3.8 in x 1.1 in (96.5 mm x 27.9 mm)

**Approval Listings:** FCC/IC, cET-

Lus Listed to UL 639, Certified to

ULC-S306

**Other Standards:** RoHS

#### Flood Detector



##### PROSIXFLOOD

**Mounting Hardware:** Included

**Probe:** Included

**LED Indicators:** Yes

**Typical Range\*:** 300 ft (92 m)

RF Frequency: 2.4 GHz

**Encryption:** 128-bit AES

**Tamper Protected:**

Cover and Wall

**Power Requirements:** 3 V

CR123A Lithium Battery, Qty 1

(Panasonic CR123A, Duracell DL123A or Huiderui CR123A)

**Operating Temperature:**

32°F to 122°F (0°C to 50°C)

**Relative Humidity:**

95 % max., non-condensing

**Dimensions (H x W x L):**

**Sensor:** 1.1 in x 1.6 in x 3.1 in (27.9 mm x 40.6 mm x 78.7 mm)

**Probe:** 0.4 in x 1.5 in x 1.0 in (10.2 mm x 38.1 mm x 25.4 mm)

**Approval Listings:** FCC/IC, cET-

Lus Listed, Conforms to ANSI/UL

2017, Certified to CAN/CSA STD

C22.2 #205

**Other Standards:** RoHS

†Please refer to the installation guide for additional details.

\*Varies based on each installation due to environmental and/or other conditions.

# FIRST ALERT® ProSeries Security and Life Safety Sensors

## Technical Specifications

(continued)

### Life Safety Sensors

#### Combination Smoke/Heat/Carbon Monoxide (CO) Detector



#### PROSIXCMBOV/ PROSIXCMBOV(Canada)

**Mounting Hardware:** Included  
**LED Indicators:** Yes  
**360° LED Ring:** Yes  
**Voice Annunciation:** English/Spanish or English/French (*Canada version only*)  
**Audible Signal:** 85 dBA  
**Heat Detection:**  $\geq 135^{\circ}\text{F}$  ( $57^{\circ}\text{C}$ )  
**Typical Range\*:** 300 ft (92 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover  
**Power Requirements:** 3 V CR123A Lithium Battery, Qty 4 (*Panasonic CR123A only*)  
**Operating Temperature:**  $32^{\circ}\text{F}$  to  $100^{\circ}\text{F}$  ( $0^{\circ}\text{C}$  to  $38^{\circ}\text{C}$ )  
**Storage Temperature:**  $14^{\circ}\text{F}$  to  $158^{\circ}\text{F}$  ( $-10^{\circ}\text{C}$  to  $70^{\circ}\text{C}$ )  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (Dia x D):** 6.2 in x 1.99 in (157.5 mm x 50.5 mm)  
**Approval Listings:** FCC/IC, ETL Listed to UL 268 (7th Edition) and UL 2075 (*only US version*); cETL Certified to ULC S531 and CSA 6.19-17 (*Canada version only*)  
**Other Standards:** RoHS  
**One-Go-All-Go:** Yes  
**End-of-Life and Clean Me Alerts:** Yes

#### Carbon Monoxide (CO) Detector



#### PROSIXCOV / PROSIXCOVCN(Canada)

**Mounting Hardware:** Included  
**LED Indicators:** Yes  
**Audible Signal:** 85 dBA  
**Typical Range\*:** 300 ft (92 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover  
**Power Requirements:** 3 V CR123A Lithium Battery, Qty 2 (*Panasonic CR123A, Duracell DL123A or Duracell DL123*)  
**Operating Temperature:**  $32^{\circ}\text{F}$  to  $100^{\circ}\text{F}$  ( $0^{\circ}\text{C}$  to  $38^{\circ}\text{C}$ )  
**Storage Temperature:**  $14^{\circ}\text{F}$  to  $158^{\circ}\text{F}$  ( $-10^{\circ}\text{C}$  to  $70^{\circ}\text{C}$ )  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (Dia x D):** 5.3 in x 1.7 in (134.6 mm x 43.2 mm)  
**Approval Listings:** FCC/IC, ETL Listed to UL 2075 (*US version only*); cETLus Listed to UL 2075, CAN/CSA 6.19 (*Canada version only*)  
**Other Standards:** RoHS  
**One-Go-All-Go:** Yes  
**End-of-Life Alert:** Yes

#### Smoke/Heat Detector



#### PROSIXSMOKEV

**Mounting Hardware:** Included  
**LED Indicators:** Yes  
**Audible Signal:** 85 dBA  
**Heat Detection:**  $\geq 135^{\circ}\text{F}$  ( $57^{\circ}\text{C}$ )  
**Rate-of-Rise (RoR):**  $> 104^{\circ}\text{F}$  ( $40^{\circ}\text{C}$ ) @  $15^{\circ}\text{F}/\text{min}$  ( $8.33^{\circ}\text{C}/\text{min}$ )  
**Typical Range\*:** 300 ft (92 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover  
**Power Requirements:** 3 V CR123A Lithium Battery, Qty 2 (*Panasonic CR123A*)  
**Operating Temperature:**  $40^{\circ}\text{F}$  to  $100^{\circ}\text{F}$  ( $4.4^{\circ}\text{C}$  to  $38^{\circ}\text{C}$ )  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (Dia x D):** 4.7 in x 2.3 in (119.4 mm x 58.4 mm)  
**Approval Listings:** FCC/IC, cETLus Listed, Certified to UL 268 and CAN/ULC S529  
**Other Standards:** RoHS, Prop 65 US, NFPA 72  
**One-Go-All-Go:** Yes  
**End-of-Life and Clean Me Alerts:** Yes

#### Heat Detector



#### PROSIXHEATV

**LED Indicators:** Yes  
**Audible Signal:** 85 dBA  
**Heat Detection:**  $\geq 135^{\circ}\text{F}$  ( $57^{\circ}\text{C}$ )  
**Rate-of-Rise (RoR):**  $> 104^{\circ}\text{F}$  ( $40^{\circ}\text{C}$ ) @  $15^{\circ}\text{F}/\text{min}$  ( $8.33^{\circ}\text{C}/\text{min}$ )  
**Typical Range\*:** 300 ft (92 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** Cover  
**Power Requirements:** 3 V CR123A Lithium Battery, Qty 2 (*Panasonic CR123A*)  
**Operating Temperature:**  $40^{\circ}\text{F}$  to  $115^{\circ}\text{F}$  ( $4.4^{\circ}\text{C}$  to  $46.1^{\circ}\text{C}$ )  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (Dia x D):** 4.7 in x 2.3 in (119.4 mm x 58.4 mm)  
**Approval Listings:** FCC/IC, cETLus Listed, Certified to UL 521 and CAN/ULC S530  
**Other Standards:** RoHS, Prop 65 US, NFPA 72  
**One-Go-All-Go:** Yes  
**End-of-Life Alerts:** Yes  
**Resettable (after alarm):** Yes

\*Varies based on each installation due to environmental and/or other conditions.

# FIRST ALERT® ProSeries Security and Life Safety Sensors

## Technical Specifications

(continued)

### Wearables

#### Two-Way Wireless Key Fob



##### PROSIXFOB

**Key Ring:** Included  
**LED Indicators:** Yes  
**Audio Sounder:** Yes  
**Typical Range\*:** 200 ft (61 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** No  
**Power Requirements:** 3 V CR2032 Lithium Coin Cell Battery, Qty 1 (*Duracell DL2032 or Maxell CR2032*)  
**Operating Temperature:** 32°F to 122°F (0°C to 50°C)  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (H x W x L):** 0.4 in x 1.4 in x 2.2 in (10.2 mm x 35.6 mm x 55.9 mm)  
**Approval Listings:** FCC/IC, ETL Listed to UL 985, UL 1023 and UL 1635, cETL Listed to ULC ORD-C1023 and ULC-S545  
Other Standards: RoHS, SIA CP-01, C-Tick

#### Personal Medical Transmitter



##### PROSIXMED

**Wearable Mode:** Belt Clip, Lanyard, or Wristband (*all included*)  
**LED Indicators:** Yes  
**Typical Range\*:** 200 ft (61 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** No  
**Power Requirements:** 3 V CR2450 Lithium Coin Cell Battery, Qty 1 (*Duracell DL2450, Panasonic CR2450 or Energizer CR2450*)  
**Operating Temperature:** 32°F to 122°F (0°C to 50°C)  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (H x W x L):** 0.6 in x 1.6 in x 1.8 in (15.2 mm x 40.6 mm x 45.7 mm)  
**Approval Listings:** FCC/IC, cETLus Listed, Conforms to UL 985, UL 1023 and UL 1637, Certified to ULC ORD-C1023 and ULC-S545  
Other Standards: RoHS

**IMPORTANT!** This wireless key is intended as a convenience to the user and should not be considered a life safety device.

#### Personal Panic Transmitter



##### PROSIXPANIC

**Wearable Mode:** Belt Clip, Lanyard, or Wristband (*all included*)  
**LED Indicators:** Yes  
**Typical Range\*:** 200 ft (61 m)  
**RF Frequency:** 2.4 GHz  
**Encryption:** 128-bit AES  
**Tamper Protected:** No  
**Power Requirements:** 3 V CR2450 Lithium Coin Cell Battery, Qty 1 (*Duracell DL2450, Panasonic CR2450 or Energizer CR2450*)  
**Operating Temperature:** 32°F to 122°F (0°C to 50°C)  
**Relative Humidity:** 95 % max., non-condensing  
**Dimensions (H x W x L):** 0.6 in x 1.6 in x 1.8 in (15.2 mm x 40.6 mm x 45.7 mm)  
**Approval Listings:** FCC/IC, cETLus Listed, Conforms to UL 985, UL 1023 and UL 1637, Certified to ULC ORD-C1023 and ULC-S545  
Other Standards: RoHS

**IMPORTANT!** This wireless key is intended as a convenience to the user and should not be considered a life safety device.

\*Varies based on each installation due to environmental and/or other conditions.

## Technical Specifications

(continued)

### Sounders

#### Indoor Siren



#### PROSIXSIREN

**LED Indicators/Strobe:** Yes

**Siren Output Level:** 85 dBA at 10 ft (3 m)

**Typical Range\*:** 300 ft (92 m)

**RF Frequency:** 2.4 GHz

**Encryption:** 128-bit AES

**Tamper Protected:** Cover and Wall

**Power Requirements:**

1.5 V AA Non-Rechargeable Lithium Battery,  
Qty 4 (Energizer)

**Operating Temperature:**

32°F to 122°F (0°C to 50°C)

**Relative Humidity:**

95 % max., non-condensing

**Dimensions (Dia x D):**

5.5 in x 1.8 in (139.7 mm x 45.7 mm)

**Approval Listings:** FCC/IC, cETLus Listed,  
Conforms to UL 985 and UL 1023, Certified to  
ULC-S545 and ULC/ORD-C1023

**Other Standards:** RoHS

**One-Go-All-Go:** Yes

#### Outdoor Siren



#### PROSIXSIRENO

**Mounting Hardware:** Included

**LED Indicators/Strobe:** Yes

**Siren Output Level:** 85 dBA at 10 ft (3 m)

**Typical Range\*:** 300 ft (92 m)

**RF Frequency:** 2.4 GHz

**Encryption:** 128-bit AES

**Tamper Protected:** Cover and Wall

**Power Requirements:**

1.5 V AA Non-Rechargeable Lithium Battery,  
Qty 4 (Energizer)

**Operating Temperature:**

-40°F to 122°F (-40°C to 50°C)

**Relative Humidity:**

95 % max., non-condensing

**Dimensions (Dia x D):**

6.0 in x 1.9 in (152.4 mm x 48.3 mm)

**Approval Listings:** FCC/IC, cETLus Listed,  
Conforms to UL 985 and UL 1023, Certified to  
ULC-S545 and ULC/ORD-C1023

**Other Standards:** RoHS

**One-Go-All-Go:** Yes

\*Varies based on each installation due to environmental and/or other conditions.

# FIRST ALERT® ProSeries Security and Life Safety Sensors

## Ordering

OR-NO	Description	OR-NO	Description
<b>PROSIXCTV</b>	Door/Window Sensor, White	<b>PROSIXCOV</b>	Carbon Monoxide (CO) Detector, White (US version only)
<b>SIXMAGWH</b>	Spare Magnet for PROSIXCTV and PROSIXSHOCK, White, 10/pack	<b>PROSIXSMOKEV</b>	Smoke/Heat Detector, White
<b>PROSIXCTV-BR</b>	Door/Window Sensor, Brown	<b>PROSIXHEATV</b>	Heat Detector, White
<b>SIXMAGBR</b>	Spare Magnet for PROSIXCTV-BR, Brown, 10/pack	<b>COVERPLATE</b>	Mounting Plate to Cover Holes, White (fits PROSIXSMOKEV and PROSIXHEATV)
<b>PROSIXMINI3</b>	Mini Door/Window Sensor, White	<b>PROSIXFOB</b>	Two-Way Wireless Key Fob, Black
<b>PROSIXMINI</b>	Mini Door/Window Sensor (Flat style), White	<b>PROSIXMED</b>	Personal Medical Transmitter, Black
<b>PROSIXPIRV</b>	Motion Detector, White	<b>PROSIXPANIC</b>	Personal Panic Transmitter, Black
<b>PROSIXSHOCK</b>	Shock Sensor, White	<b>PROSIXSIREN</b>	Indoor Siren, White
<b>PROSIXTEMP</b>	Temperature Sensor, White	<b>PROSIXSIRENO</b>	Outdoor Siren, White w/ Gray
<b>PROSIXGB</b>	Glassbreak Detector, White	<b>PROSIXCMBOVC</b>	Combination Smoke/Heat/Carbon Monoxide Detector, White (Canada version only)
<b>PROSIXFLOOD</b>	Flood Detector, White	<b>PROSIXCOCN</b>	Carbon Monoxide (CO) Detector, White (Canada version only)
<b>PROSIXCMBOV</b>	Combination Smoke/Heat/Carbon Monoxide Detector, White (US version only)		

### Replacement Batteries

#### 3 V CR123A Lithium Battery

Requires 1: PROSIXCTV, PROSIXCTV-BR, PROSIXPIRV, PROSIXSHOCK, PROSIXGB, PROSIXTEMP, PROSIXFLOOD  
 Requires 2: PROSIXCOV, PROSIXCOVCN, PROSIXSMOKEV, PROSIXHEATV  
 Requires 4: PROSIXCOMBOV, PROSIXCOMBOVC

#### 3 V CR2 Lithium Battery

Requires 1: PROSIXMINI3

#### 1.5 V AA Non-Rechargeable Lithium Battery

Requires 4: PROSIXSIREN, PROSIXSIRENO

#### 3 V CR2032 Lithium Coin Cell Battery

Requires 1: PROSIXFOB

#### 3 V CR2450 Lithium Coin Cell Battery

Requires 1: PROSIXMINI, PROSIXPANIC, PROSIXMED



### Resideo Technologies, Inc.

16100 N 71st St  
 Scottsdale, AZ 85254

#### For more information

resideo.com/pro  
 1-800-645-7492

L/PSR62WWSD/D | HDS | 05/25  
 © 2025 Resideo Technologies, Inc.

All rights reserved. The Honeywell Home trademark is used under license from Honeywell International Inc. This product is manufactured by Resideo Technologies, Inc. and its affiliates. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.

Use of the Works with Apple badge means that an accessory has been designed to work specifically with the technology identified in the badge and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.