

8MP Network LumiColor Turret Camera (2.8 mm)

N5T-8CA2



Key Features

- 8MP Turret Housing
- 2.8 mm Lens
- LumiColor With White-Light LEDs
- Video Content Analytics+: Line Crossing, Intrusion, Loitering Detection, Parking Detection
- LumiAnalytics: Face Detection, People Counting, Heat Map, Queue Management, Smart Object Detection
- iMD
- LumiPower
- LumiPolarPro and LumiDesertPro

Certifications and Compliance

- NDAA Compliant
- FCC
- IC

Learn More



Learn more about this product's key technologies.



View all compatible accessories for this product.

Overview

The **N5T-8CA2** is part of Luminys's Mainstream series of security devices. Mainstream series devices are designed with a suite of advanced LumiTechnologies to meet the needs of today's evolving security market.

Key Technologies

LumiColor technology allows you to capture color footage in complete darkness (0 lux). Cameras with this technology have integrated white-light LEDs to illuminate scenes in low lighting. The integrated white lights work in combination with a large aperture lens to capture more available light and reproduce color images with superior detail and contrast.

LumiSearch technology lets you quickly find, track, and identify targets in security footage using a reference image. The LumiSearch algorithm analyzes human body shape, clothing color, and other characteristics to accurately pinpoint where a target has appeared in footage captured by any LumiSearch-enabled camera and NVR.

LumiAnalytics is the umbrella for Face Detection, People Counting, Queue Management, Smart Object Detection, and Heat Map. These analytics use detailed metadata and advanced AI algorithms to track important metrics such as people counting and behavior analysis. These insights give businesses highly valuable information to improve and optimize operations.

LumiPower technology enables long-distance Power over Ethernet transmission, extending power and data delivery up to 3,000 feet. This simplifies installations in larger or more complex environments by eliminating the need for additional power sources or repeaters. LumiPower ensures consistent connectivity and dependable power management, ideal for expansive security infrastructures.

LumiPolarPro and **LumiDesertPro** technology ensure rugged all-weather performance. Depending on the product model, LumiPolarPro enables dependable performance in -40 °C (-40 °F) or lower, and LumiDesertPro allows operation in temperatures 60 °C (140 °F) or higher.

Specifications

Camera

Luminys Series	Mainstream
Image Sensor	1/1.8-in. 8MP Progressive CMOS
Maximum Resolution	3840 × 2160
Minimum Illumination	0.0005 Lux at F1.0 0 Lux With IR/White-Light On
Number of Illuminators	Two (2) White-Light LEDs
Illuminator Control	Automatic, Manual
Maximum Illumination Distance	Up to 30.0 m (98.4 ft)
Electronic Shutter Speed	Automatic, Manual 1/3 s to 1/100,000 s
Installation Angle	Pan: 0° to 360° Tilt: 0° to 78° Rotation: 0° to 360°
S/N Ratio	> 56 dB

Lens

Iris Type	Fixed
Lens Type	Fixed
Focal Length	2.8 mm
Maximum Aperature	F1.0
Field of View	Horizontal: 110° Vertical: 59° Diagonal: 130°
Close Focus Range	1.6 m (5.3 ft)
DORI Distance	Detect: 95.6 m (313.6 ft) Observe: 38.2 m (125.3 ft) Recognize: 19.1 m (313.6 ft) Identify: 9.6 m (31.5 ft)

Video

Compression	LumiFocus, H.265, H.264, H.264H, H.264B, MJPEG (Sub Stream Only)
Stream Capability	Three (3) Streams
Resolution	8MP (3840 × 2160), 6MP (3072 × 2048), 5MP (3072 × 1728/2592 × 1944), 4MP (2688 × 1520/2560 × 1440), 3MP (2304 × 1296/2048 × 1536), 1080p (1920 × 1080), 1.3MP (1280 × 960), 720p (1280 × 720), D1 (704 × 480), VGA (640 × 480), CIF (352 × 240)
Maximum Frame Rate	Main Stream: 3840 × 2160 at 30 fps Sub Stream 1: D1 at 30 fps Sub Stream 2: 1920 × 1080 at 30 fps
Video Bit Rate	H.265: 12 kbps to 16384 kbps H.264: 32 kbps to 16384 kbps
Bit Rate Control	CBR/VBR
Day/Night	Color, Black and White
Light Balancing	Wide Dynamic Range (120 dB)
Noise Reduction	3D NR
Image Rotation	0°/90°/180°/270° (Supports 90°/270° With 4MP Resolution and Lower)
Mirroring	Supported
Region of Interest	Four (4) Zones
Privacy Masking	Four (4) Zones

Analytics

Video Content Analytics	Line Crossing, Intrusion, Loitering Detection, Parking Detection
Intelligent Motion Detection	Supported with Alarms for Vehicles and Humans
Face Detection	Capture Snapshots and Facial Attributes
Heat Map	Supported
People Counting	Tripwire and In-Area People Counting, Queue Management With Report
LumiSearch	Supported When Used With LumiSearch-Enabled NVRs
LumiAnalytics	Supported
Object Monitoring	Supported

Audio

Compression	PCM, G.711a, G.711Mu, AAC
Interface	Input: Built-in Microphone

Alarm

Event	No SD Card, SD Card Full, SD Card Error, Network Disconnection, IP Conflict, Illegal Access, Motion Detection, Video Tampering, Voltage Detection, Security Exception, Line Crossing, Intrusion, Fast Moving, Loitering Detection, Aggregate Detection, Scene Changing, Audio Detection, Face Detection, iMD, Area People Counting, Stay Alarm, People Number Exception Detection, Object Monitoring
-------	--

Network

Interface	RJ-45 (10/100 Base-T)
Protocol	IPv4, IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, 802.1x
Interoperability	ONVIF (Profile S/G/T), API, SDK
Browser	Chrome, Firefox
Client	LumiViewer, LumiViewer Mobile App
Storage	FTP, SFTP, NAS, MicroSD Card (Max. 512 GB)

Electrical

Power Supply	12 VDC, PoE (802.3at), LumiPower
Power Consumption	12 VDC <ul style="list-style-type: none">• Maximum: 7.9 W• Normal: 3.6 W PoE <ul style="list-style-type: none">• Maximum: 9.6 W• Normal: 5.0 W


Construction

Net Weight	0.8 kg (1.7 lb)
Gross Weight	1.0 kg (2.1 lb)
Operating Temperature	-40 °C to 60 °C (-40 °F to 140 °F) < 95% RH (Non-Condensing)
Storage Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Protection Ratings	IP67
Dimensions (L × W × H)	Φ 142.0 mm × 130.0 mm (Φ 5.6 in. × 5.1 in.)
Material	Metal

Certifications and Compliance

Certifications	FCC, IC
Compliance	NDAA

Dimensional Drawing



Compatible Accessories

Below are the compatible accessories for this product. Not all accessories are included with purchase; some must be purchased separately. For each mount type, all listed SKUs are required to ensure proper installation.

Cross-check the accessories in this datasheet with the Luminy's accessory selector tool, and verify that the mount size corresponds to the camera size. Failure to check may result in an incorrect or incomplete mount.

Accessory Combination	SKU(s)	Description
Junction Box	N5T/N5P-J01 <i>(Must be Purchased Separately)</i>	Junction Box for Standard Size Turret Camera Models
Wall Mount	N5T/N5P-W01 <i>(Must be Purchased Separately)</i>	Wall Mount Bracket for Standard Size Turret Cameras
	N5T/N5P-W01 <i>(Must be Purchased Separately)</i>	Wall Mount Bracket for Standard Size Turret Cameras
Horizontal Pole Mount*	N3/N5-P01 <i>(Must be Purchased Separately)</i>	Pole Mount Bracket for Select Standard Size Bullet, Dome, and Turret Cameras
	N5T/N5P-J01 <i>(Must be Purchased Separately)</i>	Junction Box for Standard Size Turret Camera Models
Vertical Pole Mount*	N3/N5-P01 <i>(Must be Purchased Separately)</i>	Pole Mount Bracket for Select Standard Size Bullet, Dome, and Turret Cameras
	N5T/N5P-A02 <i>(Must be Purchased Separately)</i>	Adapter Plate for N5T/N5P Series Turret Cameras
Pendant Mount*	N9F/P4/P5-E01 <i>(Must be Purchased Separately)</i>	Ceiling Mount Bracket for Select Fisheye, Standard Size Turret, Multi-Directional, and PTZ Cameras

*All SKUs listed must be used to complete the mounting combination. Verify the compatibility of the listed mounting components prior to ordering. Failure to use all SKUs listed and ensure compatibility may result in an incorrect or incomplete mount.