

Illuminated Push-To-Open Bar

SD-961A-36SLQ

The ENFORCER Illuminated Push-to-Open Bar works with an external electric strike or maglock to provide egress from a protected area. It can work in stand-alone mode or as part of an access control system, but also can be locked open by key. Buzzer, output timing, and LED function and colors are also customizable.



Features:

- Provides convenient on-door egress
- LED makes it easy to see the status
- Can be stand-alone or connected to an access control system
- Dogging standard dogging with hex key
- For 36" doors actual length: 33⁷/₁₆" (85cm)
- Can be cut to fit smaller doors, minimum 23⁵/₈" (60cm)
- Two built-in non-latching (momentary), dual-contact switches (NO/NC/COM) rated at ≤5A@230VAC, adjustable 0.5~60 sec
- Large LED shows red in standby and green when triggered, but is programmable red/green/blue by an access control panel
- Blinking LED and buzzer programmable for relock warning
- Built-in buzzer indicates unlocked (selectable, up to 92dB)










Specifications:

Operating voltage		12~24 VDC
Power consumption		180mA@12VDC, 140mA@24VDC (max.)
Contact load		≤5A@230VAC
Outputs		NO/NC/COM x2
Trigger time		0.5-60 seconds (adjustable) or dogged open
Buzzer		Up to 92dB (adjustable)
LED	Colors	Stand-alone red/green, Controlled red/green/blue
Indicator	Size	8 ¹ / ₄ "x1" (210x25 mm)
Door width		36" (91.4cm), minimum 23 ⁵ / ₈ (60cm)
Operating temperature		32°~150° F (0°~70° C)
Dimensions		33 ⁷ / ₁₆ "x2 ³ / ₈ "x2 ³ / ₈ " (850x61x61 mm)
Weight		4-lb 10-oz (2.1kg)

Dimensions:



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com

(€ ∰s