# SECO-LARM<sup>®</sup>

## Access

## **Surface-Mount Electric Rim Strikes**

## **SD-998C-D3Q** 3/4" Housing Thickness **SD-998C-D3AQ** 1/2" Housing Thickness

The SECO-LARM Surface-Mount Electric Rim Strikes are designed with the strength and durability for use with rimtype exit devices with a Pullman latch bolt (<sup>3</sup>/<sub>4</sub>" throw for the SD-998C-D3Q, <sup>1</sup>/<sub>2</sub>" throw for the SD-998C-D3AQ). The strikes feature 12/24 VDC operating voltage, selectable fail-safe/fail-secure operation, horizontal adjustment, and a surface-mount metal housing, eliminating the need for frame cutting during installation.





## **Specifications**

Model	SD-998C-D3Q	SD-998C-D3AQ
Operating voltage	12/24 VDC	
Current draw	540mA@12VDC, 270mA@24VDC	
Maximum latch throw	<sup>3</sup> /4" (19mm)	<sup>1</sup> /2" (13mm)
Static strength	1,500-lb (6673N)	
Dynamic strength	70ft-lb (95J)	
Endurance	250,000 cycles (UL Tested), Level IV	
Destructive attack	Level I	
Line security	Level I	
Standby power	Level I	
Operating temperature	14°~120° F (-10°~49° C)	
Operating humidity	0~85%	
Dimensions	9"x1 <sup>3</sup> /4"x <sup>3</sup> /4" (229x45x19 mm)	9"x1 <sup>3</sup> /4"x <sup>1</sup> /2" (229x45x13 mm)

## **( E** 🕬

#### Copyright © 2025 SECO-LARM U.S.A, Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

#### SECO-LARM® *ENFORCER®* CRIMEBUSTER® CBA® *SLI® J*

PI\_SD-998C-D3xQ\_250318.docx


### **Features**


- UL 294 & UL 1034 Listed
- Tamper-resistant
- 12/24 VDC Operating voltage
- Non-polarized connection
- Horizontal adjustment
- Accommodates up to 3/4" Pullman latch
- Reversible non-handed design
- Stainless steel construction
- Surface-mount on metal or wood frames
- Works with standard rim-type exit devices including SECO-LARM SD-962AR-36A, SD-962AR-36G, SD-962BR-36A, and SD-962BR-36G
- For indoor use only
- Static strength 1,500-lb (6673N)
- Tested for 250,000 cycles (UL Tested)
- Low current draw: 540mA@12VDC, 270mA@24VDC
- Field-selectable for fail-safe or fail-secure
- Spacers included
  - SD-998C-D3Q 3x <sup>1</sup>/<sub>32</sub>" (0.9mm)
  - SD-998C-D3AQ –1x <sup>1</sup>/<sub>16</sub>", 2x <sup>1</sup>/<sub>8</sub>" (1.5mm, 3mm)


## SECO-LARM<sup>®</sup> U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606 **Phone:** (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com

### **Dimensions**







Accessories



