

Bluetooth® Access Controller

SK-B141-PQ Single-Gang Keypad with Reader

Streamlined, fully app-based setup using integrated Bluetooth® wireless technology. No codes to remember, intuitive app design for easy, visual programming. Provides convenience and security to the user and administrator. All data is secured on the device without the risks inherent with an internet connection.

Features

- No Codes to Remember Intuitive, visual app-based programming and management, 1,000 users, device options, etc.
- More Than Access Can control doors, gates, lighting, machinery, etc.
- No Internet Exposure All data secured locally on device
- Multiple User Types Permanent, scheduled, temporary, # of times
- Output Modes Timed relock, continually unlocked or locked, toggle
- User Customization Individually customizable output mode and time
- Hold Open Hold door open with code or app (customizable)
- Secure, Integrated Bluetooth Passcode protected, AES 128 encryption
- Unlimited Devices Access/manage unlimited devices with one app
- Easy Backup/Restore For off-device storage / restoration / replication
- Wrong-Code Lockout and Tamper Alarm Output Customizable
- Multilingual App Interface Currently supports English, Spanish, Portuguese, French, German, Russian, Vietnamese, and Chinese (Traditional or Simplified)







App-Based Setup



1,000 Users



SL Access™ App







App-Based Management and Control


On-Device Security

AES 128 Encryption Settings, passcodes kept on device, set by the Administrator



Administrator Settings

Set all device parameters, manage users, view audit trail, backup/restore




User Management

Add, view, import/export, customize individual settings, scheduling, output settings



Audit Trail

View most recent 1,000 events, searchable by user and type, and download for archive



Unlock with App

Users can unlock the door with the app, as well as with the keypad or prox



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com



Copyright © 2025 SECO-LARM U.S.A, Inc. All rights reserved.

All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.

The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.


Specifications


odes	App / keypad / proximity card
	1,000 users / 1 administrator
y voltage	9~25 VDC
Standby	55mA@12VDC, 30mA@24VDC
Active (max.)	100mA@12VDC, 55mA@24VDC
Form C	2.0A@30VDC
Outputs Tamper alarm	100mA@30VDC (solid state N.C.)
odes	Timed relock (1~1,800s), continually locked, continually unlocked, toggle
Egress	N.O. Ground
Door sensor	N.C. Ground
	Backlit
	y voltage Standby Active (max.) Form C Tamper alarm odes

-	
Tamper Sensor	Vibration detector
Electrical protection	Short circuit, electrostatic discharge,
	reverse polarity, relay contact protection
Bluetooth version	Bluetooth Low Energy (BLE) 4.2
Proximity frequency	EM 125kHz
IP Rating	IP65 Weatherproof
Operating humidity	0~95% non-condensing
Operating temperature	-4°~122° F (-20°~50° C)
Material	Zinc alloy with chrome plating
Dimensions	3 ¹ / ₈ "x4 ¹³ / ₁₆ "x ⁷ / ₈ " (79x123x23 mm)
Weight	1-lb 3.8-oz (560g)

Three Ways to Unlock or Trigger a Device









Unlock with the SL Access app

Unlock with a proximity card

Unlock with the keypad

Dimensions





Download the *SL Access*™ App









Android 5.0 and higher

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by SECO-LARM is under license. Other trademarks and trade names are those of their respective owners.