

Integra



Features:

- 2 Door Access Control Panels
- Mounted on a 19" Rackmount Plate
- Multi-swipe Functionality
- Distributive Processing, Built in Clock
- Connect via Serial Port, USB or Ethernet
- Flash Upgradeable Firmware
- 3,000 Cardholders & Access Levels
- 5 Card Formats per Panel Simultaneously
- Automation Links, Anti-Passback, Etc...
- Easy to use Cardholder Database
- Comprehensive Reports

Compatible Software Modules:

RBH-IRC-BB	Integrated PhotoID Module
RBH-IRC-BIO	Fully Integrated Biometric Fingerprint Module
RBH-IRC-VM	Visitor Management
RBH-IRC-CCTV	DVR Integration Suite
RBH-IRC-DT	Database Transfer Wizard
RBH-IRC-WEB	Web Client


Compatible Panels:

RBH-IRC-2000	2-Door Controllers
RBH-URC-2004	4-Door Controllers
RBH-URC-2002	2-Door Controllers for 19" Rack
RBH-URC-2005	4-Door Controllers for 19" Rack
RBH-URC-2008	Elevator Controller

Models:

URC-2003 2-reader universal reader controller
 URC-2005 4-reader universal reader controller
 URC-2003-B 2-reader universal reader controller board only

RBH-URC-2003 2 Door Rack Mountable

Networks per PC	32 (TCP/IP Ethernet or RS-485, supervised)
Controllers per Network	16
Communication Between Controllers:	Supervised RS-485
Speed	Programmable 9.6 - 56 Kbps
Distance	4,000 ft (1,200m)
Cable Type	18AWG, 2 conductor, twisted, shielded
Cards per Panel	3,000 (up to ten digit card numbers)
Access Levels per Panel	3,000 (one per card per panel)
Site Codes per Panel	10 (site code programming is not mandatory)
Offline Transactions Buffer	3,000 FIFO, command and alarm priority
Access Points (Readers / Keypads):	2 (Red, Green LED and Buzzer control)
Distance	Max 500ft (150m)
Cable Type	20-22 AWG, 6 or 8 conductor, shielded
Simultaneous Card Formats per Panel	5, Wiegand or Clock & Data
Programmable Supervised Inputs:	4
Input Supervision	Four state monitoring (1 or 2 resistors)
Distance	Max 1,000ft (300m)
Cable Type	20-22 AWG, 2 conductor
Programmable Outputs:	2 SPDT 5A @ 30 VDC, dry contacts 2 Electronic drivers, 12 VDC max, 100 mA
Output Mode	Programmable Fail Safe/ Fail Secure
Enclosure Size and Weight	W/L/H 12" x 14" x 3.25", Kit with readers 12 lbs
Power Requirements	12VDC 2A Liner Power Supply (not included)
Recommended Back-up Battery	12V, 7AH lead, acid or gel cell (not included)
Certifications	

*Specifications are subject to change without notice.



WWW.RBH-ACCESS.COM

© RBH Access Technologies, Inc. 2016