

Equipped with buttons to quickly call the concierge, open the lock, control the Do Not Disturb mode, and electronically adjust the volume.

Also, the SP-03 has a three-color light indicator of the status and operating modes of the device.

Specifications

Number of VoIP accounts supported

IPv4

1

Supported protocol type Network connection

1 PoE port IEEE 802.3af

1 PoE IEEE 802.3af port Power supply

and 1+12 V DC connection port

Supported codec type

 $G.711\mu / A$

Doorbell

Additional function

Audio transmission method

Full Duplex

Number of control keys

Configuration and programming

method

WEB-interface

White / Black Colors Overall dimensions 183 × 105 × 28 mm Installation Type Wall mounted

Main features



Concierge calling



Flexible system



Calling the lift to the floor



Quick installation



Emergency alert



Door bell connection



Do Not Disturb mode



Touch Buttons



Easy to replace with a monitor



(4) PoE powered

Functional capabilities

Calls to the Concierge Monitor

Call forwarding

SIP 2.0 protocol support, for organizing communication with any VoIP equipment supporting this protocol

Supports internal BAS-IP protocol

DND

Mute

Displaying various device statuses using LEDs

Opening the lock of the called panel

6 volume levels

Color variations




BLACK




WHITE

Appearance and mechanical mounting







Screws