



SPC-2001

USB Joystick Controller



Key features

- Superior system compatibility by CMS (SSM, Wisenet Viewer) using PC
- 3D joystick control
- Quick and easy installation
- Hall-effect 3 Axis

SPC-2001

USB Joystick Controller



Joystick		
Axis	Hall-effect 3 Axis	
Button	12ea	
Performance		
Range of Movement	X/Y-Axis	±28°
	Z Axis	±23.5°
Center	Two Spring, Two Directions	
Minimum Power	0.109 [N·m]	
Operating Power	0.151 [N·m]	
Maximum Power	0.169 [N·m]	
Materials		
Housing	ABS	
Handle	Poly Carbonate	
Cover	Rubber (Button)	
Shaft	SUM24L + Ni plating	
Interface		
Port	4-pin USB Type A	
Software		
Drivers	Standard DirectX Drivers (DirectInput)	
Electric Features		
Operating Voltage	(DC 5 [V]), Vdd = 5 [V] (±0.5 [V]) via USB	
Operating Current	50 [mA]	
Operating Environment		
Temperature	0°C to +40°C (20% ~ 85% RH)	
Materials		
Cable Length	2 [m]	
Size(WxDxH)	182 X 182 X 106 [mm]	
Weight	405g	
Color	Black	