

APC Smart-UPS SRT 2200VA RM 120V

SRT2200RMXLA

Call for More Information 800-800-4272



- Includes: CD with software, Documentation CD, Installation guide, Rack mounting brackets, Rack mounting hardware, Rack mounting support rails, USB cable, Warranty card

Output

Output power capacity	1.8kWatts / 2.2kVA
Max Configurable Power (Watts)	1.8kWatts / 2.2kVA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 2 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(6) NEMA 5-20R (1) NEMA L5-20R
Bypass	Built-in bypass

Input

Nominal Input Voltage	120V
Input frequency	40 - 70 Hz Auto-sensing
Input Connections	NEMA 5-20P
Cord Length	6ft (1.8meters)
Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Included Battery Modules	1

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS SRT 2200VA RM 120V | SRT2200RMXLA | Downloaded on 11/25/2020 (EST)

Batteries & Runtime	
Typical recharge time	3hour(s)
Nominal Battery Voltage	72 V
Replacement Battery	SRT72RMBPUS 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	102 Watts
Extendable Run Time	1
Extended Run Options	APC-Smart-UPS-SRT-2200VA-RM-120V (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, Smart-Slot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	340Joules

Physical	
Maximum Height	3.35inches (85MM, 8.5CM)
Maximum Width	17.01inches (432MM, 43.2CM)
Maximum Depth	22.99inches (584MM, 58.4CM)
Rack Height	2U
Net Weight	55.01lbs. (24.95KG)
Shipping weight	75.0lbs. (34.02KG)
Shipping Height	9.69inches (246MM, 24.6CM)
Shipping Width	23.58inches (599MM, 59.9CM)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Depth	31.89inches (810MM, 81.0CM)
Color	Black
Units per Pallet	12.0

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-20 - 50 °C
Storage Elevation	0 - 50000ft (0 - 15240meters)
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	535.0BTU/hr
Protection Class	IP20

Conformance	
Approvals	CSA C22.2 No 107.3-05, ENERGY STAR V2.0 (USA), FCC part 15 class A, OSHPD, UL 1778
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.