

APC Smart-UPS SRT 3000VA RM 120V Network Card

Featured

SRT3000RMXLA-NC

\$3,525.00*

Call for More Information 800-800-4272



- Includes: CD with software, Documentation CD, Installation guide, Network management card, Rack mounting brackets, Rack mounting support rails, USB cable, Warranty card

Output

Output power capacity	2.7kWatts / 3.0kVA
Max Configurable Power (Watts)	2.7kWatts / 3.0kVA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 2 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(8) NEMA 5-20R (1) NEMA L5-30R
Bypass	Internal bypass (automatic and manual)

Input

Nominal Input Voltage	120V
Input frequency	40 - 70 Hz Auto-sensing
Input Connections	NEMA L5-30P
Cord Length	8ft (2.4meters)
Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Included Battery Modules	1

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Batteries & Runtime	
Typical recharge time	3hour(s)
Nominal Battery Voltage	96 V
Replacement Battery	APCRBC152 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	151 Watts
Extendable Run Time	1
Extended Run Options	APC-Smart-UPS-SRT-3000VA-RM-120V-Network-Card (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB
Pre-Installed SmartSlot™ Cards	AP9631 (Available in Technical Tab on site)
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering	
Surge energy rating	340Joules

Physical	
Maximum Height	3.3inches (85MM, 8.5CM)
Maximum Width	17.0inches (432MM, 43.2CM)
Maximum Depth	25.0inches (635MM, 63.5CM)
Rack Height	2U
Net Weight	69.0lbs. (31.3KG)
Shipping weight	88.01lbs. (39.92KG)
Shipping Height	9.7inches (246MM, 24.6CM)

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Width	23.6inches (599MM, 59.9CM)
Shipping Depth	34.3inches (871MM, 87.1CM)
Color	Black
Units per Pallet	6.0

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 50000ft (0 - 15240meters)
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	805.0BTU/hr
Protection Class	IP20

Conformance	
Approvals	CSA C22.2 No 107.3-05, ENERGY STAR V2.0 (USA), FCC part 15 class A, OSHPD, UL 1778
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.