

Cleerline Simplex Rugged SSF™ drop cables are composed of a SSF™ tight buffered fiber in an overall 4.8 mm Rugged jacket, is Riser rated indoor/outdoor, and incorporates aramid water blocking yarns for strength and protection. SSF™ fiber adds extreme strength and durability at the glass level having up to 10,000x more bend and 2x to 3x times the tensile strength over traditional fibers.

Simplex Rugged SSF™ is ideal for installation both indoor and outdoors being designed for staple attachment, can be placed in ducts or indoors in riser spaces and tray installations.

Cleerline drop cables utilize Senko™ SC APC Premium grade 4.8mm connectors for reliable fiber mating with unparalleled durability.



FEATURES AND BENEFITS

- High mechanical strength, superior fatigue (Nd 30)
- Compatible with common connector systems for 9/125 Single-mode
- 900 µm tight buffered SSF™ fiber
- Integral SSF™ coating provides glass protection
- Senko SC APC Premium 4.8 mm connectors
- Exclusive 250 µm Soft Peel acrylate

COMPLIANCE

- ROHS Compliant Directive 2011/65/EU
- UL Listed Type OFNR, CSA FT4, IECA S-83-596
- SSF™ complies or exceeds the ITU-T recommendations G.657 A2, G.657 B2, and G.652 D, the IEC International Standard 60793-2-50 type B.1.3 and B.6.A&B Optical Fiber Specification

APPLICATIONS

- ISP delivery applications
- Telecommunications network
- High bandwidth networks
- FTTH (Fiber to the Home)

PART NUMBER	O.D	FIBERS	FIBER TYPE	CONNECTOR	LENGTH (FEET)	JACKET	INSERTION LOSS	RETURN LOSS
SRGDSCSC010ft-APC	4.8 mm	1	SM OS2	SC APC	10	RISER I/O	≤ -0.3 dB	≥ 60 dB
SRGDSCSC025ft-APC	4.8 mm	1	SM OS2	SC APC	25	RISER I/O	≤ -0.3 dB	≥ 60 dB
SRGDSCSC050ft-APC	4.8 mm	1	SM OS2	SC APC	50	RISER I/O	≤ -0.3 dB	≥ 60 dB
SRGDSCSC075ft-APC	4.8 mm	1	SM OS2	SC APC	75	RISER I/O	≤ -0.3 dB	≥ 60 dB
SRGDSCSC100ft-APC	4.8 mm	1	SM OS2	SC APC	100	RISER I/O	≤ -0.3 dB	≥ 60 dB
SRGDSCSC125ft-APC	4.8 mm	1	SM OS2	SC APC	125	RISER I/O	≤ -0.3 dB	≥ 60 dB
SRGDSCSC150ft-APC	4.8 mm	1	SM OS2	SC APC	150	RISER I/O	≤ -0.3 dB	≥ 60 dB

FIBER

Fibers	1
Type	9/125 Single-mode OS2
Coating	250 µm "Soft Peel" S-Type Coating
Color Coding	Per TIA/EIA 598C

JACKET

Type	Riser Rated PVC + UV (Indoor/Outdoor)
Color	Black
Outer Diameter	4.8 mm
Markings	Sequential Foot Markings
Strength Member	Aramid + water blocking yarns

PHYSICAL DATA

Storage Temperature Range	-40 °C to +70 °C
Operating Temperature Range	-40 °C to +70 °C
Min. Bend Radius, Unloaded	1 x O.D.
Rating	Riser - FT4
Crush/Impact Resistance	≥ 35N/cm

CONNECTORS

Quantity	2 ea SC APC
Manufacturer	Senko
Type	Premium 4.8 mm
Rating	UL Rate
Mating	IEC61753-1

ENVIRONMENTAL CHARACTERISTICS (SSF™ FIBER)

Temperature Dependence at 1310 nm and 1550 nm Induced Attenuation -60 °C to +85 °C	≤ 0.5 dB
Damp Heat Dependence at 1310 nm and 1550 nm Induced Attenuation at 85 °C, 85%RH, 30 days	≤ 0.5 dB
Watersoak Dependence at 1310 nm and 1550 nm Induced Attenuation at 20 °C, 30 days	≤ 0.5 dB

BACKSCATTER CHARACTERISTICS

Attenuation Directional Uniformity	≤ 0.03 dB/km
Attenuation Uniformity	≤ 0.05 dB
Group Index of Refraction	1310 nm 1.467
	1550 nm 1.468

PHYSICAL CHARACTERISTICS (SSF™ FIBER)

Core / P-coat Concentricity Error	≤ 0.5 µm
P-coat Diameter	125 ± 0.7 µm
P-coat Non-Circularity	≤ 1.0%
Acrylate Coating Diameter	245 ± 10 µm
Acrylate Coating Strip Force	≤ 100 g
Fiber Curl	≥ 2 m
Proof Test (screen level)	0.69 (100) (Gpa) (kpsi)
Dynamic Fatigue (n _a) 23°C, 41% R.H.	= 30
Length (typical)	2.2 ~ 25.2 km

OPTICAL CHARACTERISTICS (SSF™ FIBER)

Bend Induced Attenuation, 1550 nm	1 turn around a 7.5 mm radius mandrel	Typical = 0.15 dB ITU-T G.657 ≤ 0.5 dB
Bend Induced Attenuation, 1625 nm	1 turn around a 7.5 mm radius mandrel	Typical = 0.35 dB ITU-T G.657 ≤ 1.0 dB
Attenuation Coefficient	1310 nm	≤ 0.35 dB/km
	1550 nm	≤ 0.21 dB/km
Mode Field Diameter	1310 nm	8.6 ± 0.4 µm
	1550 nm	9.7 ± 0.5 µm
Cable Fiber Cut-off Wavelength	≤ 1260 nm	
Zero Dispersion Wavelength	1300 ~ 1324	
Zero Dispersion Coefficient	0.092 ps / (nm ² · km)	

COMPLIANCE

UL Listed Type OFNR, CSA FT4, ICEA S-83-596
 RoHS Compliant Directive 2011/65/EU

