

ABA Industry, Inc.

Specification for Approval

SPECIFICATION

STYLE S/FTP 22AWG x 4P (SOLID)
CAT.7A CMP

P/N TFP2204TXX

DATE 2024/05/09

EDITION 1.7

CUSTOMER APPROVE *Jimmy Chang*

TM

DATE 2024/05/15

APPROVAL	CONFIRM	MAKER
<i>Glen Lin</i>	<i>W.J. Wang</i>	<i>Benson Li</i>

ABA Industry, Inc.

Specification for Approval

ISSUE AND REVISION RECORD

REV. No.	DESCRIPTION	DATE
1.7	Modify plywood reel size.	2024/05/09



ABA Industry, Inc.

Specification for Approval

Product Part Number

- TFP2204TXX

Product Description

- S/FTP, 22AWG solid bare copper, CAT.7A, CMP
- Each pair twist with metal foil screen
- With braid wire

Product Features

- High performance of transmission.
- High quality of safety property.
- Sweep frequency up to 1000 MHz.


Application

- Structure cabling for horizontal and building backbone cable.
- Transmission of digital and analogue for data, video and audio applications.
- Metal shielded and braided providing good protection from EMI noise.
- Beyond IEEE 802.3an 10GBASE-T and legacy speeds.
- CDDI / ATM / Token Ring
- IEEE 802.3af (PoE) / IEEE 802.3at (PoE+) / IEEE 802.3bt (PoE++)

Applicable Standard

- Electrical Transmission
 - ISO/IEC 11801-1
 - IEC 61156-5 (Edition 2.1)
- Flame Test
 - NFPA 262 (CMP)
- Material and Construction
 - UL 444
 - CSA 22.2 NO.214
- EU Directive 2011/65/EU & 2015/863/EU
- EU Directive 2006/95/EC (LVD)

Sectional Drawing



All Material According To SS-00259

ABA Industry, Inc.

Specification for Approval

Material and Construction

Conductor	Material	22AWG solid bare copper	
Insulation	Material	Foam Fluorinated Ethylene Propylene (FEP)	
	Color code & diameter	Blue & white	1.46 ± 0.02 mm
		Orange & white	1.46 ± 0.02 mm
		Green & white	1.46 ± 0.02 mm
		Brown & white	1.46 ± 0.02 mm
Twisted	Description	Left hand direction	
Pair shield	Material	Al Mylar tape	
	Description	100 % coverage and aluminum side facing out	
Assembly	Description	Left hand direction	
Braid	Material	Tinned copper	
	Description	> 40 % coverage	
Jacket	Material	Low smoke flame retardant polyvinyl chloride (LSFRPVC)	
	Diameter	8.0 ± 0.3 mm	
	Thickness	0.45 ± 0.05 mm	
	Color	Per customer's request	
Marking	ELITE CAT. 7A / CLASS F _A --- E142890 S/FTP 22AWG 4PR 75C C(UL)US CMP(PCC-FT6) --- ETL VERIFIED TO ISO/IEC 11801 mmyy ¹ XXXFT Note 1: mmyy is date code.		

Usage & Environmental Condition

Temperature range	Storage & shipping	-20°C to 75°C
	Installation	0°C to 60°C
	Operation	-20°C to 75°C
Minimum bending radius		≥ 8 times of overall diameter
Maximum pulling tension		≤ 110 N

ABA Industry, Inc.

Specification for Approval

Physical & Electrical Characteristics (at 20°C)

Voltage rating	300V
Spark test	2.5 KV DC
AC leakage current through overall jacket	$\leq 10\text{mA}$ (1.5KV AC)
Cable cold bend	-20°C for 4 hr
Conductor DC resistance	$\leq 9.5 \ \Omega/100\text{m}$
Resistance unbalance	$\leq 4\%$
Dielectric strength	1.5 KV ac for 2 s
Insulation resistance	$\geq 5000 \text{ M}\Omega \cdot \text{km}$
Mutual capacitance	$\leq 5.6 \text{ nF}/100\text{m}$
Capacitance unbalance pair-to-ground	$\leq 160 \text{ pF}/100\text{m}$

Transmission Performance (at 20°C)

Frequency	IL	NEXT	PS.NEXT	ACRF	PS.ACRF	RL	Propagation Delay	Delay Skew
(MHz)	Max. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Max. ns/100m	Max. ns/100m
4	3.75	78.00	75.00	78.00	75.00	23.01	552.00	25.00
8	5.22	78.00	75.00	77.24	74.24	24.52	546.73	
10	5.82	78.00	75.00	75.30	72.30	25.00	545.38	
16	7.34	78.00	75.00	71.22	68.22	25.00	543.00	
20	8.21	78.00	75.00	69.28	66.28	25.00	542.05	
25	9.18	78.00	75.00	67.34	64.34	24.32	541.20	
31.25	10.26	78.00	75.00	65.40	62.40	23.64	540.44	
62.5	14.57	78.00	75.00	59.38	56.38	21.54	538.55	
100	18.53	75.40	72.40	55.30	52.30	20.11	537.60	
150	22.82	72.76	69.76	51.78	48.78	18.87	536.94	
200	26.47	70.88	67.88	49.28	46.28	18.00	536.55	
250	29.73	69.43	66.43	47.34	44.34	17.32	536.28	
300	32.69	68.24	65.24	45.76	42.76	17.30	536.08	
350	35.44	67.24	64.24	44.42	41.42	17.30	535.92	
400	38.01	66.37	63.37	43.26	40.26	17.30	535.80	
450	40.45	65.60	62.60	42.24	39.24	17.30	535.70	
500	42.76	64.92	61.92	41.32	38.32	17.30	535.61	
600	47.10	63.73	60.73	39.74	36.74	17.30	535.47	
700	51.13	62.72	59.72	38.40	35.40	16.63	535.36	
800	54.92	61.85	58.85	37.24	34.24	16.05	535.27	
900	58.51	61.09	58.09	36.22	33.22	15.54	535.20	
1000	61.93	60.40	57.40	35.30	32.30	15.08	535.14	

ABA Industry, Inc.

Specification for Approval

Shipping Information

Item	Dimension	Nominal net weight
Cable	305 m	23.04 kg (50.79 lb)
Plywood reel	D380 x d220 x H334 x h310 mm	2.78 kg
Pallet	1100 x1150 x110 mm	15.0 kg

Container type	Capacity of pallet	Pallet of reel	Capacity of plywood reel
20 feet	20	24/24	480
40 feet	30	24/24	720
40 feet HQ	30	24/24	720


Shipping could use standard delivery form or per customer's request.

Package information above is calculated by maximum container capacity, and for reference only.

All shipments must follow your local transportation regulation for gross weight limit.


Schematic Drawing of Reel & Package

Fumigated plywood reel.




Schematic Drawing of Package

Each package of pallet delivered with plastic wrap and packing strap.



Lower Pallet



TM

Upper Pallet