

ABA Industry, Inc.

Specification for Approval

Product Part Number

- TPM2404N35XX

Product Description

- U/UTP, 24AWG stranded bare copper, CAT.5E, CM

Product Features

- High performance of transmission.
- High quality of safety property.
- Sweep frequency up to 350 MHz.
- Reelex I carton and easy to pull out.
- Carton with one layer corrugated design providing sufficient strength and saving packaging space.


Application

- Structure cabling for patch cable.
- Transmission of digital and analogue for data, video and audio applications.
- IEEE 802.3u 100BASE-T and legacy speeds.
- CDDI / ATM / Token Ring
- IEEE 802.3af (PoE) / IEEE 802.3at (PoE+)

Applicable Standard

- Electrical Transmission
 - ANSI/TIA-568.2-D (2018)
 - ISO/IEC 11801-1
 - IEC 61156-6 (Edition 3.1)
- Flame Test
 - UL 1685 (CM)
- Material and Construction
 - UL 444
 - CSA 22.2 NO.214
- EU Directive 2011/65/EU & 2015/863/EU
- EU Directive 2006/95/EC (LVD)
- CE compliance date: 2010.01.01

Sectional Drawing



All Material According To SS-00259

Establish Date	2019.08.07	Edition	1.4	Revised Date	2022.07.27
----------------	------------	---------	-----	--------------	------------

ABA Industry, Inc.
639 EAST WALNUT STREET
CARSON, CA 90746
NEW TELEPHONE # 310-327-7670
NEW FAX # 310-808-0778
TOLL FREE 888-534-7776

ABA Industry, Inc.

Specification for Approval

Material and Construction

Conductor	Material	24AWG stranded bare copper	
Insulation	Material	Polyolefin (PO)	
	Color code & diameter	Blue & white/blue Stripe	0.93 ± 0.02 mm
		Orange & white/orange stripe	0.91 ± 0.02 mm
		Green & white/green stripe	0.92 ± 0.02 mm
		Brown & white/brown stripe	0.91 ± 0.02 mm
Twisted	Description	Left hand direction	
Assembly	Description	Left hand direction	
Jacket	Material	Flame retardant polyvinyl chloride (FRPVC)	
	Diameter	5.1 ± 0.2 mm	
	Thickness	0.50 ± 0.05 mm	
	Color	Per customer`s request	
Marking	ELITE 350 PATCH CABLE CAT 5E GIGASYSTEM---E224805-w UTP 4PR 24AWG 75°C C(UL)US CM---ETL VERIFIED TO TIA-568.2-D mmyy RoHS COMPLIANT XXXXFT Note 1: mmyy is date code.		

Usage & Environmental Condition

Temperature range	Storage & shipping	-20°C to 75°C
	Installation	0°C to 60°C
	Operation	-20°C to 60°C
Minimum bending radius		≥ 4 times of overall diameter
Maximum pulling tension		≤ 110 N

ABA Industry, Inc.

Specification for Approval

Physical & Electrical Characteristics (at 20°C)

Voltage and Temperature rating	300V / 75°C
Spark test	2.5 KV DC
AC leakage current through overall jacket	≤ 10mA (1.5KV AC)
Cable cold bend	-20°C for 4 hr
Conductor DC resistance	≤ 14.0 Ω/100m
Resistance unbalance	≤ 5%
Dielectric strength	1.5 KV ac for 2 s
Insulation resistance	≥ 5000 MΩ • km
Mutual capacitance	≤ 5.6 nF/100m
Capacitance unbalance pair-to-ground	≤ 330 pF/100m

Transmission Performance (at 20°C)

Frequency	IL	NEXT	PS.NEXT	ACR	PS.ACR	ACRF	PS.ACRF	RL	Propagation Delay	Delay Skew
(MHz)	Max. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Min. dB/100m	Max. ns/100m	Max. ns/100m
1	2.45	68.30	65.30	65.85	62.85	66.80	63.80	20.00	570.00	45.00
4	4.86	59.27	56.27	54.41	51.41	54.76	51.76	23.01	552.00	
8	6.92	54.75	51.75	47.84	44.84	48.74	45.74	24.52	546.73	
10	7.76	53.30	50.30	45.54	42.54	46.80	43.80	25.00	545.38	
16	9.90	50.24	47.24	40.34	37.34	42.72	39.72	25.00	543.00	
20	11.12	48.78	45.78	37.66	34.66	40.78	37.78	25.00	542.05	
25	12.50	47.33	44.33	34.83	31.83	38.84	35.84	24.17	541.20	
31.25	14.07	45.88	42.88	31.81	28.81	36.90	33.90	23.33	540.44	
62.5	20.39	41.36	38.36	20.97	17.97	30.88	27.88	20.74	538.55	
100	26.37	38.30	35.30	11.93	8.93	26.80	23.80	18.99	537.60	
150	33.05	35.66	32.66	N.A.	N.A.	23.28	20.28	17.47	536.94	
200	38.91	33.78	30.78	N.A.	N.A.	20.78	17.78	16.40	536.55	
250	44.22	32.33	29.33	N.A.	N.A.	18.84	15.84	15.57	536.28	
300	49.17	31.14	28.14	N.A.	N.A.	17.26	14.26	14.89	536.08	
350	53.82	30.14	27.14	N.A.	N.A.	15.92	12.92	14.31	535.92	

Values above 100MHz are for information only.

ABA Industry, Inc.

Specification for Approval

Shipping Information

Item	Dimension	Nominal net weight
Cable	305 m	9.13 kg (20.12 lb)
Reelex I Carton	L370 x W219 x H370 mm	950 g
Pallet	1100 x 1150 x 110 mm	14.1 kg

Container type	Capacity of pallet	Pallet of carton	Capacity of carton
20 feet	20	45/30	750
40 feet	40	45/30	1500
40 feet (HQ)	40	45/45	1800


Shipping could use standard delivery form or per customer's request.

Package information above is calculated by maximum container capacity, and for reference only.

All shipments must follow your local transportation regulation for gross weight limit.


Schematic Drawing of Carton

One layer corrugated Reelex I carton.




Schematic Drawing of Package

Each package of pallet delivered with plastic wrap, packing strap and paper corner protector.



Lower Pallet
Lower Pallet(HQ)
Upper Pallet(HQ)



Upper Pallet

AK001 / 210×297 / 1.1

Revised Information

Edition	Revised Description	Revised Date
1.3	Change the Package Pictures.	2022.06.06
1.4	Add Voltage rating	2022.07.27