



ULT-P4BIR 4 Megapixel IP Plug & Play Mini Bullet, 4mm, 100' IR Range, PoE/DC12V

Features

- 4 Megapixel (2688 x 1536) Resolution
- Fixed Lens
- H.264/H.264+, MJPEG Compression
- True Day/Night
- True WDR 120dB
- 100' IR Range
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Model Number	ULT-P4BIR
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm @ F2.0 (6mm optional) Angle of view: 75.8°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120db
Day & night	IR cut filter with auto switch
Video compression	H.264 / MJPEG / H.264+
Dual stream	Yes
Max. image resolution	4 MP CMOS, 2688x1520
Frame rate	20fps (2688x1520), 30fps (1920x1080)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Network Storage	NAS
BLC	Yes, zone configurable
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-22 °F ~ 140 °F (-30 °C ~ 60 °C) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 5W
Ratings	IP66
IR range	UP to 100ft
Dimensions	2.4" x 3" x 5.5" (60.9 x 3 x 139.7mm)
Weight	0.66lbs (300g)

Ordering Information

ULT-P4BIR4: 4 Megapixel, 4mm

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

4 MEGAPIXEL PLUG & PLAY