



Quality Products. Service Excellence.

Type 3R Painted Galvanized Steel Wallmount Enclosure *C3R HCRMD*

Series

Continuous Hinge Door with Screws



Application

- Designed for use as a wiring/junction box.
- Provides protection against rain, sleet, snow and dripping water.

Standards

- UL-50 Type 3R
- CSA Type 3R
 - Complies with
 - NEMA Type 3R
 - IEC 60529, IP24

Construction

- Formed and spot welded from 16 or 14 gauge galvanized steel.
- Drip shield top and seam-free sides, front and back.
- Stainless steel continuous hinge.
- Cover fastened with captive plated screws.
- Padlocking hasp.
- Collar studs provided for mounting optional panels.
- External mounting feet.
- Oil resistant gaskets are permanently secured.

Finish

- Enclosure and cover are finished inside and out in ANSI 61 gray powder coating.

Accessories

- Additional Inner Panels
- Swing Panel Kit
- Ventilation

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

| Part No. | Enclosure | | | Optional Inner Panel | | |
|-------------|-----------|-------|------|----------------------|-------|-------|
| | H | W | D | Part Number | H | W |
| C3R16126HCR | 16.00 | 12.00 | 6.00 | 18P1309 | 13.00 | 9.00 |
| C3R16166HCR | 16.00 | 16.00 | 6.00 | 18P1313 | 13.00 | 13.00 |
| C3R18186HCR | 18.00 | 18.00 | 6.00 | 18P1515 | 15.00 | 15.00 |

| Part No. | Enclosure | | | Optional Inner Panel | | |
|--------------|-----------|-------|-------|----------------------|-------|-------|
| | H | W | D | Part Number | H | W |
| C3R20166HCR | 20.00 | 16.00 | 6.00 | 18P1713 | 17.00 | 13.00 |
| C3R20208HCR | 20.00 | 20.00 | 8.00 | 18P1717 | 17.00 | 17.00 |
| C3R24208HCR | 24.00 | 20.00 | 8.00 | 18P2117 | 21.00 | 17.00 |
| C3R24248HCR | 24.00 | 24.00 | 8.00 | 18P2121 | 21.00 | 21.00 |
| C3R30248HCR | 30.00 | 24.00 | 8.00 | 18P2721 | 27.00 | 21.00 |
| C3R30308HCR | 30.00 | 30.00 | 8.00 | 18P2727 | 27.00 | 27.00 |
| C3R181810HCR | 18.00 | 18.00 | 10.00 | 18P1515 | 15.00 | 15.00 |
| C3R242410HCR | 24.00 | 24.00 | 10.00 | 18P2121 | 21.00 | 21.00 |
| C3R302410HCR | 30.00 | 24.00 | 10.00 | 18P2721 | 27.00 | 21.00 |
| C3R363610HCR | 36.00 | 36.00 | 10.00 | 18P3333 | 33.00 | 33.00 |
| C3R303012HCR | 30.00 | 30.00 | 12.00 | 18P2727 | 27.00 | 27.00 |
| C3R362412HCR | 36.00 | 24.00 | 12.00 | 18P3321 | 33.00 | 21.00 |
| C3R363012HCR | 36.00 | 30.00 | 12.00 | 18P3327 | 33.00 | 27.00 |
| C3R423012HCR | 42.00 | 30.00 | 12.00 | 18P3927 | 39.00 | 27.00 |
| C3R363612HCR | 36.00 | 36.00 | 12.00 | 18P3333 | 33.00 | 33.00 |
| C3R423612HCR | 42.00 | 36.00 | 12.00 | 18P3933 | 39.00 | 33.00 |
| C3R483612HCR | 48.00 | 36.00 | 12.00 | 18P4533 | 45.00 | 33.00 |
| C3R603612HCR | 60.00 | 36.00 | 12.00 | 18P5733 | 57.00 | 33.00 |
| C3R303016HCR | 30.00 | 30.00 | 16.00 | 18P2727 | 27.00 | 27.00 |
| C3R483616HCR | 48.00 | 36.00 | 16.00 | 18P4533 | 45.00 | 33.00 |

Tags: C3R, NEMA 3R, Type 3R, galvanized steel, painted steel, knockouts, junction box, wiring box, continuous hinge, screw cover, mounting feet *Data subject to change without notice*

© 2026. Hammond Manufacturing Ltd. All rights reserved.