


CAT 6 600MHz UTP CABLE

DIRECT BURIAL OUTDOOR (GEL PE)

Cable Detail



Applicable Standards

- UL444 (Mechanical Properties only)
- TIA-568-C.2
- RoHS Compliant



Physical Characteristics

Conductor Material	Solid Bare Copper
Number of Conductors	4
AWG	23 AWG
Stranding	Solid
Fill Type	Gel
Insulation Material	HDPE
Overall Diameter	0.040 in. ± 0.0002 in.
Average Thickness	0.0010 in.
Jacket Material	LLDPE, Sunlight Resistant
Average Wall Thickness	0.03 in.
Nominal Outer Diameter	0.027 in. ± 0.019 in.
Nominal Weight	39 lbs.
Shielding (Y/N)	No
Ripcord (Y/N)	Yes
Separator (Y/N)	Yes

Mechanical Characteristics

Temperature Range	Installation	0°C to + 75°C
	Operating	-20°C to + 75°C
Tensile Strength	Before	≥ 19 Mpa
Elongation	Aging	≥ 300%
Aging Condition		100°C x 96 hours
	After	≥ 85% of unaged
	Aging	≥ 50% of unaged

Insulation Colors

Pair 1	White / Blue	Blue
Pair 2	White / Orange	Orange
Pair 3	White / Green	Green
Pair 4	White / Brown	Brown

Part Numbers

Jacket Color

Package

6EOSPGBK2N

Black

1000FT / Reel

Electrical Characteristics

DC Resistance	9.38 Ω / 100m Max. @ 20°C
Resistance Unbalanced	5% Max. @ 20°C
Capacitance Unbalance	330 pF / 100m Max. @ 20°C
Mutual Capacitance	5.6 nF / 100m Max. @ 20°C
Delay Skew	45 nS / 100m Max. @ 20°C
Nominal Velocity of Propagation (NVP)	69%

Electrical Performance

Frequency (MHz)	Attenuation (dB/100m) Max.	Return loss (dB) Min.	NEXT (dB) Min.	PS-NEXT (dB) Min.
1	2.0	20.0	77.3	75.3
4	3.8	23.6	68.3	66.3
8	5.3	25.4	63.8	61.8
10	5.9	26.0	62.3	30.3
16	7.4	26.0	59.3	57.3
20	8.3	26.0	57.8	55.8
25	9.3	25.5	56.3	54.3
31.25	10.4	25.0	54.9	52.9
62.5	14.9	23.5	50.4	48.4
100	19.0	22.5	47.3	45.3
155	23.9	21.6	45.8	43.5
200	27.4	21.0	42.8	40.8
250	30.8	20.5	41.3	39.3
300	34.0	20.1	40.2	38.2
350	37.0	19.8	39.2	37.2
400	39.7	19.5	38.3	36.3
450	42.1	19.2	37.5	35.5
500	44.9	19.0	36.8	34.8
550	47.3	18.8	36.2	34.2
600	50.7	15.7	44.2	42.2
Frequency (MHz)	ELFEXT (dB/100m) Min.	PS-ELFEXT (dB) Min.	ACR (dB) Min.	PS-ACR (dB) Min.
1	70.8	67.8	75.0	73.0
4	58.7	55.7	64.0	62.0
8	52.7	49.7	57.7	55.7
10	50.8	47.8	55.6	53.6
16	46.7	43.7	50.7	48.7
20	44.7	41.7	48.2	16.2
25	42.8	39.8	45.6	13.6
31.25	40.9	37.9	42.8	40.8
62.5	34.8	31.8	32.9	30.9
100	30.8	27.8	24.9	22.9
155	27.0	23.6	21.0	21.5
200	24.7	21.7	18.4	16.4
250	22.8	19.8	13.5	11.5
300	21.2	18.2	9.6	5.0
350	19.9	16.9	5.2	3.2
400	18.7	15.7	1.5	-
450	17.7	14.7	-	-
500	16.8	13.8	-	-
550	15.9	12.9	-	-
600	N/A	N/A	N/A	N/A

* Values above 250MHz are information only.

Cable Marking

CATEGORY 6 600MHZ 23AWG 4PR UTP DIRECT BURIAL OUTDOOR GEL FILLED TIA-568-C.2 *****FT

