

Product Code

F01412

7" WAY KIT MONITOR 1

Reference

1412

EAN

8424299014128

Description.

Description

New Monitor Way.

Choose from 20 different melodies, customize monitor settings, record videos and capture images of your visits.

- Intercommunication: Establishes communication between the monitors installed inside the home.
- Player: After 3 seconds, the monitor automatically records a video (if a micro SD card is installed) or a photo of the visitors. You also have the option to manually take a photo while answering the call. The videos/photos recorded from the entrance panel are displayed on the monitor screen.
- Settings: Brightness/contrast, melody selection, date and time, day and night call volume, language selection (16 languages), etc.
- “Do not disturb” function: 1 hour, 8 hours or permanently.
- Call log: All calls, both from the panel to the monitor, from the monitor to the panel and between monitors, are recorded and can be reviewed later.
- Capacitive touch screen: 7” color TFT digital monitor with capacitive touch screen that allows intuitive use.

Technical Details

Monitor Specifications:

- Power supply for the monitor: DC 24~28V.
- Power consumption: Standby 12mA; 350mA operation.
- Monitor screen: 7” color digital TFT. Capacitive screen.
- Video signal: 1 Vpp, 75Ω, CCIR standard.
- Wiring: 2 wires, non-polarized.
- Dimensions: 225(H) x 131(V) x 18(D)mm.
- Operating temperature: [-20ºC, +55ºC]

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
131x225x18	0.6522	4x24,2x16,5	WAY

Manuals

- 97833g Anadir Monitor Secundario KIT WAY V06_17.pdf
- 97833IKg Anadir Monitor Secundario KIT WAY V06_17.pdf

Declaration of conformity

- DOCF01412EN.pdf