

Product Code
F09264

DUOX PLUS IRIS SMART WIFI 7" MONITOR

Reference
9264

EAN
8424299092645

Description.

Description

Equipped **with Wi-Fi connectivity that allows call diverting to mobile devices** . Thanks to the Fermax DuoxMe app, available free on the Play Store and App Store, the video intercom's functions can be managed directly from a mobile phone or tablet, allowing you to connect to your home wherever you are.

Hands-free monitor. It features a slim, extra-thin design. Thanks to its OSD menu, 7" touchscreen, and push-button layout, user interaction is simple and intuitive. Made of high-impact ABS plastic. Textured finish for easy cleaning and UV protection for greater sunlight resistance.

It includes a 7" (16:9) widescreen color touchscreen. Its balanced design with pure lines is distinctive, modern, and minimalist. It blends into the environment. When a call is received, the image appears automatically. When the conversation button is pressed, the conversation with the visitor begins. The image disappears automatically after 90 seconds or when the button is pressed again. To open the door, press the key button.

Up to 5 spaces configurable by the installer for displaying web pages. Navigation between spaces using gestures.
Compatible with NXT Server ref. 1251.

ACCESSORIES:

CONNECTOR

- 9447 DUOX PLUS MONITOR CONNECTOR (the monitor is compatible with version V1 and V2 of the connector ref. 9447).
- For mounting the monitor on the wall surface.

Technical Details

GENERAL FEATURES

- **Technology:** DUOX PLUS (full digital 2-wire non-polarized)
- **Audio/Video System:** Color Audio/Video
- **Mounting:** Surface-mounted (connector ref. 9447 to be requested separately). The monitor is compatible with versions V1 and V2 of connector ref. 9447.
- **Desktop stand (optional):** Yes (ref. 9420 / ref. 9247)
- **Hands-free communication:** Yes
- **Optional Press-to-talk communication:** Yes
- **Inductive loop:** No
- **Screen dimensions:** 7" (16:9 Panoramic) IPS
- **Screen resolution (H x V):** 1024 x 600
- **Product Color:** White
- **Total buttons:** 2
- **Button type:** Mechanical
- **Number of LEDs for visual signaling:** 5 (power, wifi, missed calls, doormatic, do not disturb)

TERMINAL ADDRESS PROGRAMMING

- **From the terminal:** Via OSD menu
- **From the panel or concierge:** Yes
- **From the panel using the doorbell (without entering the home):** Yes
- **From DUOX decoders**

FUNCTIONS

- **Manual or automatic photo capture (PHOTOCALLER):** Yes (Up to 150 photos, 368 x 288 pixels). User-activated function. Disabled by default
- **Manual or automatic video capture (VIDEOCALLER):** Yes (Up to 10 videos of 15 sec. duration). User-activated function. Disabled by default
- **Concierge call:** Yes (from door opening button)
- **Auto power-on:** Yes (up to 3 panels/cameras)
- **On-screen OSD menu:** Yes
- **Additional Function F1:** Yes (send negative and/or command). Installer-configurable icon.
- **Additional Function F2:** Yes (command only, no negative). Installer-configurable icon.
- **Distinct doorbell melody:** Yes
- **Connection for additional devices (call extensions, light and bell activation, etc.):** Yes (ref. 2040)
- **Additional terminals with the same address:** Yes, up to 2 additional terminals (may require additional power supply)
- **Doormatic (professional door opening function):** Yes (configurable up to 12 hours). With LED indicator icon

- **IP camera display:** Yes (up to 4 IP cameras with RTSP streaming). Photo and video capture and F1/F2 activation. Compatible with ref. 9986 / Auxiliary WiFi IP Camera
- **Intercom function for calling other monitors in the same home. Call-To-All or Selective call. Up to 90 sec. conversation**

SETTINGS

- **Date and time:** Yes
- **Melody selection:** Yes. Configurable for Block 0 Panel, Block 1 Panel, General Entry Panel 0, and Concierge.
- **Ringing volume adjustment:** Yes (10 levels via OSD menu)
- **Do not disturb function:** Yes (via OSD menu) + LED icon signaling
- **Conversation audio volume adjustment:** Yes
- **Brightness, contrast, and color adjustment:** Yes (via OSD menu)

TECHNICAL SPECIFICATIONS

- **Product dimensions (Width x Height x Depth mm):** 190 x 155 x 15.5. *When the monitor is mounted on the connector, the total protrusion from the wall is 19 mm.*
- **Response or door opening time from call:** 30 s
- **Conversation time:** 90 s
- **Conversation privacy:** Yes
- **Power supply voltage:** 18-24 Vdc
- **Maximum consumption (W):** 12 W . Installations without decoder ref. 9419 or 9425: up to 12 monitors per power supply ref. 4825. Installations with decoder ref. 9419 or 9425: one power supply per decoder
- **Operating temperature (°C, °F); Humidity:** [-10ºC, +55ºC]; [0%, 95%]
- **Line adapter included in the monitor:** Yes (A, C, default position OFF)
- **Terminals:** Bin, Bin, Bout, Bout, -, A+, F1, T

CALL DIVERSION (APP FOR MOBILES & TABLETS)

- **Call diversion to smartphones and tablets:** Yes
- **Connectivity:** Wifi (2.4 GHz)

Compatibility with DUOX 3.0 and earlier installations cannot be guaranteed in all cases.

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
0.55182	2,7x20,5x16	DUOX

Manuals

- 970351b Guia Rapida Monitor IRIS Smart 7 DUOX PLUS V07_26 (194X297).pdf

Declaration of conformity

- DOCF09264EN.pdf

Accessories



F09247
UNIVERSAL DUOX DESKTOP SUPPORT



F03389
UNIVERSAL FRAME LARGE

Video

- https://www.youtube.com/playlist?list=PLf1YNFmssC35L8dw6Z1YwrCCDXryXJ0Jb